

Astra



Features IP65


- Surface mounted light effect luminaire.
- Body is made of die cast aluminium, with toughened thermal shock glass diffuser or focused convex lens, weatherproof durable silicone gasket and external screws made of stainless steel.
- Superior polyester powder paint resistant to outdoor atmospheric conditions.
- Front cover is designed to avoid accumulation of dust and water.
- Simple to install with 2 cable entries to facilitate through wiring.
- Easy relamping via Allen screws.
- Light sources include Metal Halide.
- Fixtures are available in 3 light distributions: symmetric, narrow or flood, and asymmetric.
- Superpure aluminium reflector or focused convex lens for beam light effects.
- Designed and manufactured to comply with European standard EN 60598.

Applications

- The simple modernistic appearance of Astra Wall mounted luminaire makes it ideal for today architectural developments and with Up/Down light version that gives special narrow beam light effect for a personalized application or with floodlight asymmetric version providing a high level of illuminance on the illuminated surface.
- Application areas: suitable to solve many lighting task including safety and security, facades, entrances, walkways, corridors, outdoor or indoor.




Colour 10 29



Astra Up & Down

3300	70W	G12	CDM-T	M.H.			60° & 60°
3214	150W	G12	CDM-T	M.H.			60° & 60°


With integral electronic control gear 220-240V 50/60Hz.



Astra Up or Down

3301	70W	G12	CDM-T	M.H.			60°
3217	150W	G12	CDM-T	M.H.			60°


With integral electronic control gear 220-240V 50/60Hz.



Astra Up & Down

3302	70W	G12	CDM-T	M.H.			8° & 60°
3190	150W	G12	CDM-T	M.H.			8° & 60°


With integral electronic control gear 220-240V 50/60Hz.



Astra Up & Down Narrow

- 3303** 70W G12 CDM-T M.H. 8° & 8°
- 3189** 150W G12 CDM-T M.H. 8° & 8°


With integral electronic control gear 220-240V 50/60Hz.



Astra Up & Down Asymmetric

- 3297** 2x35W G12 CDM-T M.H.


With integral electronic control gear 220-240V 50/60Hz



Astra Up or Down Narrow

- 3304** 70W G12 CDM-T M.H. 8°
- 3191** 150W G12 CDM-T M.H. 8°

With integral electronic control gear 220-240V 50/60Hz.




Astra Up or Down Asymmetric

- 3187** 150W RX7s HIT-DE M.H.

With integral electronic control gear 220-240V 50/60Hz



Accessories





2508 Pole mounted bracket set

Ø 102mm

2507 Pole mounted bracket set

Ø 120mm

With connector for one fixture.
Available in colours 10, 29.



2563 Pole mounted bracket set

Ø 102mm

2564 Pole mounted bracket set

Ø 120mm

With connector for two fixtures.
Available in colours 10, 29.

