



BADGE

design R. Fiorato, F. Pagliarini



A range of indoor/outdoor wall luminaires, with aluminium base and frosted glass cover. BADGE luminaires come in two different sizes, and are designed exclusively for use with white LEDs, signalling and high power versions.

The reduced depth of the fixtures allows them to be used as an alternative to similar recess mounted luminaires. BADGE is suitable for decorative and accent lighting in homes, display and commercial area lighting.

BADGE

BADGE 150

	36 LED - 2,5 W
	5 LED - 5,5 W

BADGE 230

	100 LED - 7 W
	9 LED - 10 W

Series of wall mounting luminaires for indoor and outdoor use, comprising:

- Base in die-cast aluminium, painted white
- Frame in sandblasted, chrome-plated die-cast aluminium
- Pressed glass cover, internally frosted
- Silicone foam gasket
- Stainless steel locking screws
- Models are available with either 36 or 100 LED, 12 V DC or with 5 or 9 LED at 350 mA
- Available accessories: 12 V 10 W transformer / 350 mA 16 W converter



BADGE 150, 36 LED



BADGE 150, 5 LED



BADGE 230, 100 LED



BADGE 230, 9 LED



description	colour	code
-------------	--------	------

Driver kit with current 220/240 V 350 mA 5/18 W		310149
Driver kit with voltage 220/240 V 12 V DC 10 W		310148

lampholder	W	ILCOS	colour	class	IP	Kelvin	$\text{Cos } \varphi \geq 0,9$	EEL	code	notes
------------	---	-------	--------	-------	----	--------	--------------------------------	-----	------	-------

BADGE 150

	5 LED - 5,5 W	CR1+WHL	III	55	• 6000	IK07 2J xx5			300253	
	36 LED - 2,5 W	CR1+WHL	III	55	• 6000	IK07 2J xx5			300252	


BADGE 230

	9 LED - 10 W	CR1+WHL	III	55	• 6000	IK07 2J xx5			300251	
	100 LED - 7 W	CR1+WHL	III	55	• 6000	IK07 2J xx5			300250	

If information about Kelvin degrees is provided, this means that the lamp is included.

CR1+WHL

BADGE 150



BADGE 230

