

Bullet



Related products:



BULLET
P.414-417



Art . 3033

Features IP66


- Ceiling recessed downlight.
- Ring and back plug cover are made of die cast aluminium.
- Central housing is made of aluminium extrusion, with toughened safety glass, weatherproof durable silicone gasket and external screws made of stainless steel.
- Superior polyester powder paint resistant to outdoor atmospheric conditions.
- Fixture is available in 2 sizes.
- Ceiling installation via clamping wings for ceiling thickness 1 to max.30mm.
- Electrical installation includes double cable entry for through wiring.
- Easy relamping via Allen screws.
- Art. 3033 is adjustable with a 0°-20° tilting angle on each vertical side.
- Light sources include Halogen, Compact Fluor., Metal Halide and LED.
- Long life LED light source provide IR and UV free emission.
- Superpure aluminium reflector with different beam optics.
- Designed and manufactured to comply with European standard EN 60598.

Applications

- Application areas: exterior canopies, buildings, entrances, covered walkways, as well as warehouses with high ceilings, garages, workshops and factories.



Ø 158



Bullet Recessed

3107	70W G12 CDM-T M.H.		15°
3108	70W G12 CDM-T M.H.		40°
3109	70W PAR30 CDM-R M.H.		40°
3110	26W GX24q-3 TC-TE		

Control gear not included. To be ordered separately.



3497-K30D15	With 30W LED 3000K 1800lm		15°	LED
3497-K40D15	With 30W LED 4000K 2000lm		15°	
3497-K30D30	With 30W LED 3000K 1800lm		30°	
3497-K40D30	With 30W LED 4000K 2000lm		30°	
3497-K30D45	With 30W LED 3000K 1800lm		45°	
3497-K40D45	With 30W LED 4000K 2000lm		45°	

Passive dissipation, inclusive of remote driver 220-240V 50/60Hz.

CRI>80.

Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.



Ø 118



Mini Bullet Recessed

3030	7W E27 PAR20 LED		
-------------	------------------	--	--



3031	35W E27 PAR20 CDM-R M.H.		
3111	35W G8.5 CDM-TC M.H.		10°
3032	35W G8.5 CDM-TC M.H.		40°
3263	20W GX10 MR16 M.H.		

Control gear not included. To be ordered separately.



3499-K30D25	With 20W LED 3000K 1000lm		25°	LED
3499-K40D25	With 20W LED 4000K 1100lm		25°	
3499-K30D45	With 20W LED 3000K 1000lm		45°	
3499-K40D45	With 20W LED 4000K 1100lm		45°	
3499-K30D55	With 20W LED 3000K 1000lm		55°	
3499-K40D55	With 20W LED 4000K 1100lm		55°	

Passive dissipation, inclusive of remote driver 220-240V 50/60Hz.

CRI>80.

Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.



Ø 118



Mini Bullet Recessed Adjustable

3033	35W GU5.3 MR16 Hal.		20°
-------------	---------------------	--	-----

Adjustable Angle +/- 20°.

Transformer not included. To be ordered separately.



Accessories



2605	Waterproof Box IP66 26W (EL) TC
2648	Waterproof Box IP66 20W (EL) HIT
2602	Waterproof Box IP66 35W (EL) HIT
2603	Waterproof Box IP66 70W (EL) HIT

With electronic control gear 220-240V 50/60Hz. For details, please see p.426.



2352	Waterproof box IP67 75VA 12V
-------------	------------------------------

With electronic transformer 220-240/12V 50/60Hz. For details, please see p.426.