

Coco




Related products:



ROLO
Track
P.172-173

ROLO
Mini Track
P.192-193

ROLO
Wall/Ceiling
P.248-249



Features IP20



- Track mounted spotlight with versatile aiming angle 0°-180° vertical tilting 350° horizontal rotation adjustability.
- Light head and control gear case are made of die cast aluminium.
- Track adaptor - three circuit universal.
- Fixture is available in 2 different sizes and 2 designs, Horizontal and Vertical.
- Light sources include Low Voltage Halogen, Metal Halide and LED.
- Superpure aluminium reflector with different optic beam.
- Easy relamping via removable front housing by snap-in catch action and acceptance of optical accessories.
- Long life LED light source providing IR and UV free emission.
- LED optical grade metalized polycarbonate reflector with different beam optics.
- Designed and manufactured to comply with European standard EN 60598.

Applications

- Coco is a track lighting system concept of a wide selections of spotlights, designed to achieve the highest possible performance. The cylinder shape makes it a classic design that is easily integrated into various architectural environments. Coco is available in a variety of options of light source to allow the true beauty of objects being lighted to stand out.
- Application areas: retail, department stores, galleries, shopping centers, showrooms, residential, restaurants, hotels, exhibitions, window displays.



Colour 11 75



Coco Horizontal

6211	20W G8.5 CDM-TC M.H.		10°
6212	20W G8.5 CDM-TC M.H.		25°
6250	20W G8.5 CDM-TC M.H.		40°
6213	35W G8.5 CDM-TC M.H.		10°
6214	35W G8.5 CDM-TC M.H.		25°
6251	35W G8.5 CDM-TC M.H.		40°
6215	70W G8.5 CDM-TC M.H.		10°
6216	70W G8.5 CDM-TC M.H.		25°
6252	70W G8.5 CDM-TC M.H.		40°



Safety glass included.

With integral electronic control gear 220-240V 50/60Hz.

6372-K30D16	With 26W LED 3000K 2000lm		16°	LED
6372-K40D16	With 26W LED 4000K 2200lm		16°	
6372-K30D30	With 26W LED 3000K 2000lm		30°	
6372-K40D30	With 26W LED 4000K 2200lm		30°	
6372-K30D60	With 26W LED 3000K 2000lm		60°	
6372-K40D60	With 26W LED 4000K 2200lm		60°	

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80.

Leading-Trailing edge dimmable driver option upon request. Other colour temperatures K or CRI are available upon request.



Mini Coco Horizontal

6217	35W GX10 MR16 M.H.		20°
-------------	--------------------	--	-----

With integral electronic control gear 220-240V 50/60Hz.

6218	35W GU5.3 MR16 Hal.		20°
-------------	---------------------	--	-----


Max. 15W GU5.3 MR16 LED

With integral electronic transformer 220-240/12V 50/60Hz. Dimmable version is available upon request.

6387-K30D20	With 15W LED 3000K 1100lm		20°	LED
6387-K40D20	With 15W LED 4000K 1200lm		20°	
6387-K30D30	With 15W LED 3000K 1100lm		30°	
6387-K40D30	With 15W LED 4000K 1200lm		30°	
6387-K30D40	With 15W LED 3000K 1100lm		40°	
6387-K40D40	With 15W LED 4000K 1200lm		40°	

Passive dissipation, inclusive of integral driver 100-240V 50/60Hz. CRI>80.


Leading-Trailing edge dimmable driver option upon request. Other colour temperatures K or CRI are available upon request.



Coco Vertical


6220	20W G8.5 CDM-TC M.H.		10°
6223	20W G8.5 CDM-TC M.H.		25°
6253	20W G8.5 CDM-TC M.H.		40°
6221	35W G8.5 CDM-TC M.H.		10°
6224	35W G8.5 CDM-TC M.H.		25°
6254	35W G8.5 CDM-TC M.H.		40°
6222	70W G8.5 CDM-TC M.H.		10°
6225	70W G8.5 CDM-TC M.H.		25°
6255	70W G8.5 CDM-TC M.H.		40°

Safety glass included.
With integral electronic control gear 220-240V 50/60Hz.



6373-K30D16	With 26W LED 3000K 2000lm		16°	LED
6373-K40D16	With 26W LED 4000K 2200lm		16°	
6373-K30D30	With 26W LED 3000K 2000lm		30°	
6373-K40D30	With 26W LED 4000K 2200lm		30°	
6373-K30D60	With 26W LED 3000K 2000lm		60°	
6373-K40D60	With 26W LED 4000K 2200lm		60°	

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz.
CRI>80.
Leading-Trailing edge dimmable driver option upon request.
Other colour temperatures K or CRI are available upon request.




Mini Coco Vertical

6226	20W GX10 MR16 M.H.		
-------------	--------------------	--	--

With integral electronic control gear 220-240V 50/60Hz.

6227	35W GU5.3 MR16 Hal.		
	Max. 15W GU5.3 MR16 LED		

With integral electronic transformer 220-240/12V 50/60Hz.
Dimmable version is available upon request.



6388-K30D20	With 15W LED 3000K 1100lm		20°	LED
6388-K40D20	With 15W LED 4000K 1200lm		20°	
6388-K30D30	With 15W LED 3000K 1100lm		30°	
6388-K40D30	With 15W LED 4000K 1200lm		30°	
6388-K30D40	With 15W LED 3000K 1100lm		40°	
6388-K40D40	With 15W LED 4000K 1200lm		40°	

Passive dissipation, inclusive of integral driver 100-240V 50/60Hz.
CRI>80.
Leading-Trailing edge dimmable driver option upon request.
Other colour temperatures K or CRI are available upon request.

Accessories Table

Coloured Filters Colours 25, 42, 55, 85	Refractor Colour 41	Honeycomb Louvre Colour 10

Light Source

Coco

G8.5 CDM-TC		2659	2658	2657
-------------	--	-------------	-------------	-------------

21W LED

Mini Coco

GU5.3 MR16		2670	2671	2672
------------	--	-------------	-------------	-------------

GU5.3 MR16 LED				2672
----------------	--	--	--	-------------

GX10 MR16				
-----------	--	--	--	--

15W LED				
---------	--	--	--	--