Coco Colour







formalighting

Coco Track

Track mounted spotlight

Features

- Versatile aiming angle 0°-180° vertical tilting and 350° horizontal rotation adjustability.
- → Housing in die cast aluminium.
- → Control gear case is made of die cast aluminium.
- → Reflector made of super pure anodized aluminium.
- → Integrated Metal Halide electronic control gear or electronic transformer.

 → Track adaptor - three circuit universal.
- → Designed and manufactured to comply with European standard EN 60598.


Applications


- → A concept in spotlight design with continuous line applications for benefit of increasing the possibility of display lighting.
- → Application areas: retail, department stores, galleries, shopping centers, showrooms, residential, restaurants, hotels, exhibitions, window displays.



Coco Horizontal

Spot 10°	Flood 25°	Wide Flood 40			
6211	6212	6250	20W	G8.5 CDM-TC Metal halide	<u>-04</u>
6213	6214	6251	35W	G8.5 CDM-TC Metal halide	-
6215	6216	6252	70W	G8.5 CDM-TC Metal halide	====







Coco Horizontal

6217 35W Gx10 MR16 Metal halide

IP20 ⊕ 😿 🤇 €

6218 50W 230V/12V GU5.3 MR16 年

10W 230V/12V GU5.3 MR16 LED

Dimmable version is available on request.

IP20 ⊕ 🔻 🧲





Coco Vertical

	Spot 10°	Flood 25°	Wide Flood 40°	•		
	6220	6223	6253	20W	G8.5 CDM-TC Metal halide	=
	6221	6224	6254	35W	G8.5 CDM-TC Metal halide	#
Ī	6222	6225	6255	70W	G8.5 CDM-TC Metal halide	=

IP20 ⊕ 🔻 🕻 € Safety Glass Included





Coco Vertical

6226 20W GX10 MR16 Metal halide

IP20 ⊕ 🔻 🕻 €

6227 50W 230V/12V GU5.3 MR16

10W 230V/12V GU5.3 MR16 LED

Dimmable version is available on request.

IP20 ⊕ ₹ (€



formalighting