

# Conos Due

Designed by **Franco Mirezzi** (Registered)



## Related products:



**CONOS**  
P.174-177

**CONOS DUE**  
Wall  
P.244-247

**CONOS DUE**  
Ceiling  
P.244-247

**CONOS**  
**SUSPENSION**  
P.292-293



## Features

IP20/IP40


- Track mounted spotlight with versatile aiming angle of 0°-90° vertical tilting with 350° horizontal rotation adjustability.
- Light head is made of die cast aluminium. The control gear housing is made of heat resistance thermoplastic.
- Track adapter is the three circuit universal.
- Fixture is available in 3 different sizes.
- Easy relamping via removable front housing by snap-in catch action.
- Provides user with ultimate flexibility of firm lamp position and acceptance of optical accessories.
- Light sources include Halogen, Metal Halide and LED.
- Long life LED light source provides IR and UV free emission.
- LED Optical grade metalized polycarbonate reflectors with different beam optics are available.
- Super pure aluminium reflectors with different beam optics are available.
- Designed and manufactured to comply with European standard EN 60598.

## Applications

- Conos Due is a crisp design offering systems beyond the ordinary lighting that makes a difference. Within the scope of our systems we offer track spot, suspended and wall mounted designs using a variety of lamp options to permit the lighting to integrate most efficiently achieving a lighting solution that responds optically and architecturally to the needs and goal of its users.
- Application areas: retail, department stores, galleries, shopping centers, showrooms, residential, restaurants, hotels, exhibitions, window displays.



Colour



## Conos Due

<b>6137</b>	70W G12 CDM-T M.H.		10°
<b>6138</b>	70W G12 CDM-T M.H.		40°

Safety glass included.  
With integral electronic control gear 220-240V 50/60Hz.  
IP40

<b>6139</b>	70W E27 PAR30 CDM-R M.H.		
<b>6142</b>	70W GX8.5 CDM-R111 M.H.		

With integral electronic control gear 220-240V 50/60Hz.  
**6140** 12W E27 PAR30 **LED**


IP20

<b>6141</b>	75W G53 AR111 Hal.		
	15W G53 AR111 <b>LED</b>		

With integral electronic transformer 220-240/12V 50-60Hz.  
IP20

<b>6318-K30D15</b>	With 45W <b>LED</b> 3000K 4500lm		15°	
<b>6318-K40D15</b>	With 43W <b>LED</b> 4000K 4500lm		15°	
<b>6318-K30D24</b>	With 45W <b>LED</b> 3000K 4500lm		24°	
<b>6318-K40D24</b>	With 43W <b>LED</b> 4000K 4500lm		24°	
<b>6318-K30D36</b>	With 45W <b>LED</b> 3000K 4500lm		36°	
<b>6318-K40D36</b>	With 43W <b>LED</b> 4000K 4500lm		36°	

Active dissipation, inclusive of integral driver 220-240V 50/60Hz.  
CRI>80.  
Leading-Trailing edge dimmable driver option upon request.  
Other colour temperatures K or CRI are available upon request.  
IP20



## Mini Conos Due

<b>6303</b>	20W G8.5 CDM-TC M.H.		10°
<b>6304</b>	20W G8.5 CDM-TC M.H.		40°

Safety glass included  
With integral electronic control gear 220-240V 50/60Hz  
IP40

<b>6048</b>	35W GU5.3 MR16 Hal.		
	Max. 15W GU5.3 MR16 <b>LED</b>		

With integral electronic transformer 220-240V 50/60Hz.  
IP20


<b>6049</b>	35W GU10/GZ10 Hal.		
	6W GU10/GZ10 <b>LED</b>		

**6075** 7W E27 PAR20 **LED**

IP20

<b>6305</b>	20W GX10 MR16 M.H.		
<b>6306</b>	20W E27 PAR20 CDM-R M.H.		

With integral electronic control gear 220-240V 50/60Hz  
IP20
























## Micro Conos Due

<b>6117</b>	35W GU5.3 MR16 Hal.		
	Max. 15W GU5.3 MR16 <b>LED</b>		

With integral electronic transformer 220-240/12V 50/60Hz.  
IP20

**Accessories Table**

					
	<b>Coloured Filters</b> Colours 25, 42, 55, 85	<b>Refractor</b> Colour 41	<b>UV Filter</b> Colour 41	<b>Honeycomb Louvre</b> Colour 10	<b>Ceiling Base</b> Colour 10
<b>Light Source</b>					
<b>Conos Due</b>					
G12 CDM-T 	<b>2153</b>	<b>2155</b>	<b>2157</b>	<b>2367</b>	<b>2049</b>
E27 PAR30 CDM-R 				<b>2367</b>	<b>2049</b>
E27 PAR30 LED 				<b>2367</b>	<b>2049</b>
G53 AR111 				<b>2367</b>	<b>2049</b>
G53 AR111 LED 					<b>2049</b>
GX8.5 CDM-R111 				<b>2367</b>	<b>2049</b>
45/43W LED					
<b>Mini Conos Due</b>					
G8.5 CDM-TC 	<b>2154</b>	<b>2156</b>	<b>2158</b>	<b>2368</b>	<b>2049</b>
E27 PAR20 LED 					<b>2049</b>
E27 PAR20 CDM-R 					<b>2049</b>
GU5.3 MR16 				<b>2368</b>	<b>2049</b>
GU5.3 MR16 LED 				<b>2368</b>	<b>2049</b>
GU10/GZ10 				<b>2368</b>	<b>2049</b>
GU10/GZ10 LED 					
GX10 MR16 				<b>2368</b>	<b>2049</b>
<b>Micro Conos Due</b>					
GU5.3 MR16 	<b>2083</b>	<b>2113</b>		<b>2357</b>	<b>2049</b>
GU5.3 MR16 LED 				<b>2357</b>	<b>2049</b>

