

# Cornetto

Designed by **Franco Mirezzi**



## Features

IP65

- Wall/ceiling/pole/bollard mounted system.
- The base of the diffuser, the housed ribbed LED dissipator and top canopy are made of die cast aluminium.
- Toughened vandal proof prismatic diffuser is made of polycarbonate thermoplastic.
- The pole is made of extruded aluminium.
- With weatherproof silicone gasket and concealed stainless steel screws.
- Superior polyester powder paint is resistant to outdoor atmospheric conditions.
- Designed for an indirect light technique have the reflector and canopy with inner white finish.
- The pole/bollard version fixtures are available in different heights.
- Easy relamping via Allen screws.
- Light sources include Halogen, Compact Fluorescent, M. H. and LED.
- Long life LED light source provides IR and UV free emissions.
- Anchor bolt kit for concrete foundation installation is available as accessory.
- Designed and manufactured to comply with European standard EN 60589.

## Applications

- Cornetto has a strong design appeal that will enhance all modern and classic environments for residential and/or commercial applications.
- Designed for an indirect light application with reflector and the canopy with inner white finish to efficiently emit the light back with no glare with good optical control of brightness for visual comfort and uniformity due to its excellent prismatic lens technique design. The LED version includes a die cast aluminium ribbed base to optimize dissipation of heat to enable a longer lifetime for the LEDs.
- Application areas: landscapes, parks, walkways, pathways, entrances, walls, golf courses, gardens and bridges.




Colour 10 29



## Cornetto Wall

<b>3439</b>	20W G8.5 CDM-TC M.H.	
<b>3440</b>	35W G8.5 CDM-TC M.H.	
With integral electronic control gear 220-240V 50/60Hz.		
<b>3470</b>	57W E27 Hal.	
	14W E27 CFL	
	14W E27 LED	
<b>3441-K30</b>	With 10W LED 3000K 850lm	
<b>3441-K40</b>	With 10W LED 4000K 1050lm	
Passive dissipation, inclusive of integral driver 100-240V 50/60Hz. CRI>80.		
Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.		

LED



## Cornetto Bollard

<b>3442</b>	20W G8.5 CDM-TC M.H.		H: 600
<b>3443</b>	35W G8.5 CDM-TC M.H.		H: 600
<b>3445</b>	20W G8.5 CDM-TC M.H.		H: 1100
<b>3446</b>	35W G8.5 CDM-TC M.H.		H: 1100
<b>3448</b>	20W G8.5 CDM-TC M.H.		H: 2000
<b>3449</b>	35W G8.5 CDM-TC M.H.		H: 2000
With integral electronic control gear 220-240V 50/60Hz.			
<b>3471</b>	57W E27 Hal.		H: 600
	14W E27 CFL		H: 600
	14W E27 LED		H: 600
<b>3472</b>	57W E27 Hal.		H: 1100
	14W E27 CFL		H: 1100
	14W E27 LED		H: 1100
<b>3473</b>	57W E27 Hal.		H: 2000
	14W E27 CFL		H: 2000
	14W E27 LED		H: 2000
<b>3444-K30</b>	With 21W LED 3000K 2000lm		H: 600
<b>3444-K40</b>	With 21W LED 4000K 2200lm		H: 600
<b>3447-K30</b>	With 21W LED 3000K 2000lm		H: 1100
<b>3447-K40</b>	With 21W LED 4000K 2200lm		H: 1100
<b>3450-K30</b>	With 21W LED 3000K 2000lm		H: 2000
<b>3450-K40</b>	With 21W LED 4000K 2200lm		H: 2000
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI >80.			
Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.			

LED

## Accessories



### 2601 Anchor Bolt Kit

In steel.  
To ditch in concrete.