

# Corolla

Designed by **Franco Mirezzi**



## Features

- Wall and pole mounted light system.
- Made of die cast and extruded aluminium with tempered glass diffuser, weatherproof silicone gasket and stainless steel screws.
- Superior polyester powder paint is resistant to outdoor atmospheric conditions.
- Electrical installation option for single or double cable entry.
- Easy relamping via Allen screws.
- Light sources include Compact Fluorescent and LED.
- Long life LED light source provides IR and UV free emissions.
- Anchor bolt kit for concrete foundation installation is available as accessory.
- Designed and manufactured to comply with European standard EN 60589.


## Applications

- Corolla is an outdoor lighting system for residential and/or commercial applications, it has various mounting alternative on wall or on a post, with symmetrical lighting distribution using different light sources to illuminate upwards or downwards on the ground providing optimal visual comfort.
- Application areas: landscapes, parks, walkways, pathways, walls, entrances, golf courses, gardens and bridges.

IP65




Colour 10 29



## Corolla Surface Mounted

3259	13W	GX53	CFL			
3260-K30D25	With 6x1W LED	LED	3000K	280lm	25°	LED
3260-K63D25	With 6x1W LED	LED	6300K	330lm	25°	
3507-K30D15	With 10W LED	LED	3000K	700lm	15°	
3507-K40D15	With 10W LED	LED	4000K	820lm	15°	
3507-K30D28	With 10W LED	LED	3000K	700lm	28°	
3507-K40D28	With 10W LED	LED	4000K	820lm	28°	
3507-K30D40	With 10W LED	LED	3000K	700lm	40°	
3507-K40D40	With 10W LED	LED	4000K	820lm	40°	


Passive dissipation, inclusive of integral driver 100-240V 50/60Hz. CRI>80.  
 Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request.  
 Other colour temperatures K or CRI are available upon request.



## Corolla Bollard 1

3254	13W	GX53	CFL			
3252-K30D25	With 6x1W LED	LED	3000K	280lm	25°	LED
3252-K63D25	With 6x1W LED	LED	6300K	330lm	25°	
3508-K30D15	With 10W LED	LED	3000K	700lm	15°	
3508-K40D15	With 10W LED	LED	4000K	820lm	15°	
3508-K30D28	With 10W LED	LED	3000K	700lm	28°	
3508-K40D28	With 10W LED	LED	4000K	820lm	28°	
3508-K30D40	With 10W LED	LED	3000K	700lm	40°	
3508-K40D40	With 10W LED	LED	4000K	820lm	40°	

Passive dissipation, inclusive of integral driver 100-240V 50/60Hz. CRI>80.  
 Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request.  
 Other colour temperatures K or CRI are available upon request.



## Corolla Bollard 2

3255	2x13W	GX53	CFL			
3253-K30D25	With 2x6x1W LED	LED	3000K	2x280lm	25°	LED
3253-K63D25	With 2x6x1W LED	LED	6300K	2x330lm	25°	
3509-K30D15	With 2x10W LED	LED	3000K	2x700lm	15°	
3509-K40D15	With 2x10W LED	LED	4000K	2x820lm	15°	
3509-K30D28	With 2x10W LED	LED	3000K	2x700lm	28°	
3509-K40D28	With 2x10W LED	LED	4000K	2x820lm	28°	
3509-K30D40	With 2x10W LED	LED	3000K	2x700lm	40°	
3509-K40D40	With 2x10W LED	LED	4000K	2x820lm	40°	

Passive dissipation, inclusive of integral driver 100-240V 50/60Hz. CRI>80.  
 Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request.  
 Other colour temperatures K or CRI are available upon request.

## Accessories



### 2601 Anchor Bolt Kit

In steel.  
 To ditch in concrete.