




CRICKET 26 QUICK is a family of circular recessed in-ground fittings, designed to take the load and impact from motor vehicles and pedestrians. Quick versions are supplied complete with lamps factory fitted to speed up and maintain integrity during installation. Available in the following versions:  
 CRICKET 26 Quick/AL – with aluminium ring painted.  
 CRICKET 26 Quick/I – with aluminium ring coated in stainless steel AISI 316 and flat glass,  
 CRICKET 26 Quick features:  
 - variety of light sources  
 - reflectors available with narrow beam (C INT), wide beam (C W) and extra wide beam (C EW) distributions.  
 - vertical adjustable lamp / reflector unit  $\pm 10^\circ$  (not for C EW optic)  
 - horizontal adjustability of the fixture at  $360^\circ$   
 - Quick easy adjustable levelling system allows movement of the fitting to ensure a flush finish to ground during installation.

- Technopolymer body and outer recessing enclosure provides high corrosion resistance and stability in variable ambient temperatures.
- Toughened safety clear float glass IK10 (21 Joule).
- Anti-ageing silicone gasket, single piece (no joints), provides high flexibility and recovery to maintain IP67 rating.
- Die-cast aluminium ring, sandblasted and phosphor-chromate pre-treatment, (AL) or with AISI 316 stainless steel surface bonding (I).
- High performance and purity (99.85%) aluminium pre-anodised and polished reflectors.
- Conventional magnetic control gear suitable for 230V / 50Hz supply (other voltages and frequencies available on request). Electronic control gear suitable for 220-240V 50/60Hz supply.
- External screws in stainless steel.



### CRICKET 26 Quick/C Extra Wide

Lampholder	W	Icos	*K	Optic	Colour	Class	Wiring	EEI = $\geq 0,9$	Cosp Code	Notes	T max °C
G24q-2	18W	FSQ	$\bigcirc 2.700^\circ$	C EW	96	II	ETRCL A2		• <b>07035896</b>		51°
G24q-2	18W	FSQ	$\bigcirc 2.700^\circ$	C EW	04	II	ETRCL A2		• <b>07035904</b>		51°
G24q-2	18W	FSQ	$\bigcirc 4.000^\circ$	C EW	96	II	ETRCL A2		• <b>07032396</b>		51°
G24q-2	18W	FSQ	$\bigcirc 4.000^\circ$	C EW	04	II	ETRCL A2		• <b>07032704</b>		51°
GX24q-3	42W	FSMH	$\bigcirc 2.700^\circ$	C EW	96	II	ETRCL A2		• <b>07036096</b>		87°
GX24q-3	42W	FSMH	$\bigcirc 2.700^\circ$	C EW	04	II	ETRCL A2		• <b>07036104</b>		87°
GX24q-3	42W	FSMH	$\bigcirc 4.000^\circ$	C EW	96	II	ETRCL A2		• <b>07032496</b>		87°
GX24q-3	42W	FSMH	$\bigcirc 4.000^\circ$	C EW	04	II	ETRCL A2		• <b>07032804</b>		87°



- Complete with electronic ballast non dimmable 220-240v 50/60hz.
- Fittings supplied complete with lamp.




### CRICKET 26 Quick/C Extra Wide

Lampholder	W	Icos	*K	Optic	Colour	Class	Wiring	EEI = $\geq 0,9$	Cosp Code	Notes	T max °C
E27	50W	ST	$\bigcirc 2.000^\circ$	C EW	96	II	CRL		• <b>07032196</b>		80°
E27	50W	ST	$\bigcirc 2.000^\circ$	C EW	04	II	CRL		• <b>07032504</b>		80°
E27	70W	ST	$\bigcirc 2.000^\circ$	C EW	96	II	CRL		• <b>07032296</b>		97°
E27	70W	ST	$\bigcirc 2.000^\circ$	C EW	04	II	CRL		• <b>07032604</b>		97°


### CRICKET 26 Quick/ C INT

Lampholder	W	Icos	*K	Optic	Colour	Class	Wiring	EEI = $\geq 0,9$	Cosp Code	Notes	T max °C
RX7s	70W	MD	$\bigcirc 3.000^\circ$	C INT	96	II	CRL		• <b>07036296</b>		116°
RX7s	70W	MD	$\bigcirc 3.000^\circ$	C INT	04	II	CRL		• <b>07036304</b>		116°
RX7s	70W	MD	$\bigcirc 4.200^\circ$	C INT	96	II	CRL		• <b>07036496</b>		116°
RX7s	70W	MD	$\bigcirc 4.200^\circ$	C INT	04	II	CRL		• <b>07036504</b>		116°



### CRICKET 26 Quick/C Wide

Lampholder	W	Icos	*K	Optic	Colour	Class	Wiring	EEI = $\geq 0,9$	Cosp Code	Notes	T max °C
RX7s	70W	MD	$\bigcirc 3.000^\circ$	C W	96	II	CRL		• <b>07036696</b>		110°
RX7s	70W	MD	$\bigcirc 3.000^\circ$	C W	04	II	CRL		• <b>07036704</b>		110°
RX7s	70W	MD	$\bigcirc 4.200^\circ$	C W	96	II	CRL		• <b>07036896</b>		110°
RX7s	70W	MD	$\bigcirc 4.200^\circ$	C W	04	II	CRL		• <b>07036904</b>		110°



- Fittings supplied complete with lamp.
- Version with adjustable lamp position.

# Quick!

FAST INSTALLATION: See model numbers for fittings supplied complete with lamp.

				<b>IK 10 21 J</b>		max 7,7kg					
<b>CLASS II</b>		<b>96</b>	<b>04</b>	<b>IP 67</b>				<b>FSQ</b> 18W DULUX-D/E PL-C 4pin	<b>FSMH</b> 42W PL-T 4pin DULUX-T/E	<b>ST</b> 50-70W NAV-T Super SON-T Plus	<b>MD</b> Max 70W HCI-TS CDM-TD
							M20 Ø7-Ø12 H07RN-F 2x2,5 H07RN-F 1x2,5 2x2,5mm <sup>2</sup>			Max 2500Kg 5 kN 50 Nm	

## INSTALLATION

CRICKET 26 QUICK recessed in-ground fitting may be subjected to heavy loads and impact from pedestrians / motor vehicles during operation. To ensure optimum performance and safety it is important that the fittings are correctly installed by suitably qualified person, in strict accordance with the manufacturers installation instructions. Fittings should not be installed in a hollow or submerged underwater, they should be provided with proper drainage by means of a gravel sump, or drain pipe, ≥30cm below the bottom of the fitting. We recommend the use of H07RN-F 2x1.5 / 2x2.5 Ø7-12mm cables only.

When installing fittings within public access it is advisable to be aware of the glass surface temperatures indicated (T max °C) and confirm measurements at rated voltage are in accordance with national and local standards.

CRICKET 26 QUICK when correctly installed into concrete are designed to withstand a maximum static load of 2500 Kg or a maximum travelling load, by vehicles with pneumatic tyres, of 7500 kg gross weight at a maximum speed of 30 km/h. If installed into soil they are suitable for a maximum gross weight of 300 kg.

(T max °C)

<b>OK</b>	<b>OK</b>	<b>NO</b>
<b>OK</b>	<b>NO</b>	

50m Max

	18W	42W	50W	70W
2 x1,5 mm <sup>2</sup>	60	26	20	14
2 x2,5 mm <sup>2</sup>	90	44	32	25

## ACCESSORIES



Code	Denomination	Description
<b>14136920</b>	A0561/AL	Frosted glass for a reduced glare more comfortable light emission (voor CRICKET 26 Quick / 96).
<b>14137020</b>	A0561/I	Frosted glass for a reduced glare more comfortable light emission (voor CRICKET 26 Quick / 04).
<b>14137120</b>	A0562/AL	Frosted glass supplement to be ordered together with fitting for factory fitted option (voor CRICKET 26 Quick / 96).
<b>14137220</b>	A0562/I	Frosted glass supplement to be ordered together with fitting for factory fitted option (voor CRICKET 26 Quick / 04).
<b>14018320</b>	A0235	Rubber cable H07RN8-F 2x1.5 mm <sup>2</sup> supplied and sold in 1 metre units.
<b>14051720</b>	A0323	Anti-tearing M20x1.5 cable gland kit for through wiring connection

