

CRICKET 26

design Silvia Paola Pennacchio



CRICKET 26 circular IP67 recessed in-ground fittings designed to take the load and impact from pedestrians and motor vehicles. Suitable for highlighting buildings / houses, architectural features and details, historical buildings, façades, columns, and public areas etc. CRICKET 26 has a choice of cover rings: CRICKET 26 / Inox (04) - Stainless steel ring. CRICKET 26 / AL (96) - Aluminium ring painted aluminium grey. With a range of light sources, accessories and adjustable lamp positioning CRICKET 26 is suitable for a variety of design applications.


- PVC sump with polyamide cover flange.
- Extruded aluminium corrosion resistant and heat dissipating body with polyamide (PA 66 F.V.) ends.
- Glass bezel frame available in aluminium (AL) or stainless steel (Inox).
- Toughened "safety" glass.
- Silicone anti-ageing gaskets.
- A2 stainless steel external screws.

Options for through wiring connection using accessory A0154.



CRICKET 26 18/42 FLUO

Lampholder	W	Ilcos	*K	Optic	Colour	Class	Wiring	EEl =	Cosp ≥ 0,9	Code	Notes	Tmax °C
GX24d-2	18W	FSQ		C A	04	II	CR	B2	•	05086904		50°
GX24d-2	18W	FSQ		C A	94	II	CR	B2	•	05013898		50°
GX24q-3/4	26 - 32 - 42W	FSQ/FSMH		C	04	II	ETRC	A2	•	05086804		50°/75°
GX24q-3/4	26 - 32 - 42W	FSQ/FSMH		C	94	II	ETRC	A2	•	05014198		50°/75°




Complete with electronic ballast non dimmable 220-240v 50/60hz.

Self adjustable from symmetric to asymmetric.



CRICKET 26 35/70

Lampholder	W	Ilcos	*K	Optic	Colour	Class	Wiring	EEl =	Cosp ≥ 0,9	Code	Notes	Tmax °C
E27	70W	ST		C A	04	II	CR		•	05087304		130°
E27	70W	ST		C A	94	II	CR		•	05015098		130°
G12	35W	MT		C A	04	II	CR		•	05087404		78°
G12	35W	MT		C A	94	II	CR		•	05052194		78°
G12	70W	MT		C A	04	II	CR		•	05087504		105°
G12	70W	MT		C A	94	II	CR		•	05015998		105°



Self adjustable from symmetric to asymmetric.

Adjustable lamp positions: 2 symmetric + 2 asymmetric.



				IK 08 6J										
CLASS II		94	04	IP 67		ST 70W NAV-T/SON-T	MT 35+70W CDM-T HCL-T HQ-T	FSQ 18W DULUX D-E PL-C 2Pin	FSQ 26W DULUX D-E PL-C 4Pin	FSMH 32-42W DULUX T-E PL-T 4Pin				
	<table border="1"> <thead> <tr> <th>Mod.</th> <th>Hmm</th> <th>Ø</th> </tr> </thead> <tbody> <tr> <td>CRICKET 26 71-72-36</td> <td>640</td> <td>270</td> </tr> <tr> <td>CRICKET 26 42-18</td> <td>510</td> <td>270</td> </tr> </tbody> </table>	Mod.	Hmm	Ø	CRICKET 26 71-72-36	640	270	CRICKET 26 42-18	510	270				
Mod.	Hmm	Ø												
CRICKET 26 71-72-36	640	270												
CRICKET 26 42-18	510	270												

INSTALLATION

CRICKET 26 circular IP67 recessed in-ground fittings may be subjected to heavy load and impact from pedestrians and motor vehicles during use. For optimum performance and safety it is important that they are correctly installed by a suitable qualified person, in strict accordance with the manufacturer installation instructions

CRICKET 26 are designed to withstand a maximum static load of 5000Kg or a maximum travelling load, by motor vehicles with pneumatic tyres, of 12000Kg gross weight at a maximum speed of 30Km/h.

The fittings must not be located in a hollow or submerged underwater.

The fittings should be seated on a gravel sump, of approximately 450 mm depth from base of fitting, to allow for water drainage.

When installing fittings within public access it is advisable to be aware of the glass temperatures indicated (T max °C) and confirm measurements at rated voltage are in accordance with national and local standards.

A0157 wire guards accessory (not suitable for vehicles to be driven over). To maintain IP67 integrity, use H07RN-F 2x2,5 mm² Ø10-14 mm cables only.

	18W Gx24d-2	70W Gx24q-3/4	35W G12	70W E27/G12
H07RN-F	n°60	n°26	n°28	n°14
2x1,5mm ²	n°90	n°44	n°48	n°25

ACCESSORIES



Code	Denomination	Description
14000801	A0157	Stainless steel wire guard finished black. Protects against direct human contact with the glass (not suitable for vehicles to be driven over).
14449996	A0123 AL-I	Frosted glass suitable.
14027720	A0253 AL-I	CRICKET26 supplement for frosted glass factory fitted. To be ordered as a separate item along with fitting.
14020120	A0237	Low-emission filter glass fits behind standard glass cover to reduce external glass temperature.
14448996	A0122	Internal anti-glare steel mesh.
14000599	A0154	Anti-tearing PG 16 cable gland kit for through wiring connection.
14053720	A0337	Rubber cable H07RN-F 2x2,5mm ² supplied and sold in 1 metre units.
14076820	A0383	1 metre unit cable H07RN-F 2x2,5 mm ² supplied inside the luminaire package.

