

Cubetto



Related products:



CUBOX
P.420-421

Features IP20


- Surface mounted light effect luminaire.
- Body is made of die cast aluminium with slots and opal glass diffuser.
- Fixtures are available in 5 different light effect and light beam distribution versions.
- Easy G9 light source relamping via removable front lamp housing by snap-in catch action.
- Light sources include Halogen and LED.
- Long life LED light source provides IR and UV free emission.
- Designed and manufactured to comply with European standard EN 60598

Applications


- Cubetto wall mounted luminaire has a simple modernistic appearance making it ideal for today's architectural developments. With its Up/Down light version techniques it gives that special narrow beam light effect for a personalized application.
- Application areas: suitable to solve many lighting task including safety and security, facades, entrances, walkways, corridors retail, department stores, galleries, restaurants, hotel, lobbies.



Colour 11 75




Cubetto S1

1030 40W G9 Hal. 
2 slots: one upwards, one downwards.




1164-K30 With 3W LED 3000K 110lm **LED**
1164-K68 With 3W LED 6800K 130lm

2 slots: one upwards, one downwards.
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz.
CRI>80.
Other colour temperatures K or CRI are available upon request.





Cubetto S2

1031 40W G9 Hal. 
4 slots: two upwards, two downwards.




1165-K30 With 3W LED 3000K 110lm **LED**
1165-K68 With 3W LED 6800K 130lm

4 slots: two upwards, two downwards.
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz.
CRI>80.
Other colour temperatures K or CRI are available upon request.




Cubetto SG

1032 40W G9 Hal. 
1 slot, 1 glass diffuser.




1166-K30 With 3W LED 3000K 110lm **LED**
1166-K68 With 3W LED 6800K 130lm

1 slot, 1 glass diffuser.
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz.
CRI>80.
Other colour temperatures K or CRI are available upon request.




Cubetto G1

1033 40W G9 Hal. 
1 glass diffuser.




1167-K30 With 3W LED 3000K 110lm **LED**
1167-K68 With 3W LED 6800K 130lm

1 glass diffuser.
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz.
CRI>80.
Other colour temperatures K or CRI are available upon request.



Cubetto G2

1034 40W G9 Hal. 
2 glass diffusers, upwards and downwards.



1168-K30 With 3W LED 3000K 110lm **LED**
1168-K68 With 3W LED 6800K 130lm

2 glass diffusers, upwards and downwards.
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz.
CRI>80.
Other colour temperatures K or CRI are available upon request.