

Cubox



Related products:



CUBETTO
P.340-341

Features


IP54

- Wall mounted grazing light.
- Body is made of die cast aluminium, toughened thermal shock clear glass diffusers, weatherproof durable silicone gasket with external screws made of stainless steel.
- Superior polyester powder paint resistant to outdoor atmospheric condition.
- Wall versions available in Dual light emission with also narrow beam upward or with single light emission.
- Simple to install via cable entry.
- Light sources include Compact Fluorescent and LED.
- Long life LED light source provide IR and UV free emission.
- Designed and manufactured to comply with European standard EN 60598.

Applications


- Cubox wall is in shape of a cube with Dual lights emission; it is available also with option of narrow beam upward, the Single light emission Cubox has a minimal size.
- Application areas: suitable for illuminating doorway entrances, corridors, walkways, gateposts and columns can be used indoor or outdoor.

Colour 10 29





Cubox S1

- | | | | |
|-----------------|-----------------------------|-----|--|
| 3474-K30 | With 2x1.5W LED 3000K 140lm | 15° | |
| 3474-K65 | With 2x1.5W LED 6500K 165lm | 15° | |
- 2 slots: one upwards, one downwards.
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz.
CRI>80.
Other LED colours or CRI upon request.




Cubox SG

- | | | | |
|-----------------|-----------------------------|------------------------|--|
| 3414-K30 | With 2x1.5W LED 3000K 140lm | 100°(up) & 15° (down) | |
| | With 2x1.5W LED 3000K 140lm | 15° (up) & 100°(down) | |
| 3414-K65 | With 2x1.5W LED 6500K 165lm | 100°(up) & 15° (down) | |
| | With 2x1.5W LED 6500K 165lm | 15° (up) & 100°(down) | |
- 1 slot, 1 glass diffuser.
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz.
CRI>80.
Other LED colours or CRI upon request.



Cubox G2


- | | | | |
|-----------------|-----------------------------|------|--|
| 3415-K30 | With 2x1.5W LED 3000K 140lm | 100° | |
| 3415-K65 | With 2x1.5W LED 6500K 165lm | 100° | |
- 2 glass diffusers, upwards and downwards.
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz.
CRI>80.
Other LED colours or CRI upon request.



Cubox L1

- | | | | |
|-------------|-----------------|------|--|
| 3417 | 1x13W GX53 CFL | 100° | |
| | 1x1.5W GX53 LED | 100° | |
- One glass diffuser, downwards.

Accessories



- | | |
|-------------|--------|
| 2064 | Slot 1 |
|-------------|--------|
- Available in colour 79