

# Disco



## Related products:



**CIRCO** P.36-39    **QUADRO** P.36-39    **CIRCO Wall** P.334-335    **QUADRO Wall** P.336-337    **ORBIT Round** P.386-387    **ORBIT Square** P.386-387    **GALA** P.384-385

**Features** IP66


- Wall/Ceiling luminaries.
- Body and satin opal diffuser are made of injection molded vandal resistance polycarbonate with durable silicon gasket.
- External frame is made in aluminium with countersunk external screws made of stainless steel.
- Superior polyester powder paint is resistant to outdoor atmospheric conditions.
- Available in 3 sizes.
- Simple to install with 2 cable entries to facilitate through wiring.
- Relamping via Allen screws and easy click system removable diffuser.
- Light sources include Fluorescent, Compact and LED.
- Long life LED light source provide IR and UV free emission.
- Dimmable and Emergency versions available upon request.
- Designed and manufactured to comply with European standard EN 60598.

## Applications

- Disco include large size up to 685mm diameter surface mounted wall or ceiling luminaire to provide large areas of uniform and high quantity of light output. Easy installation and maintenance due to the click system design diffuser made of UV-resistance polycarbonate. Integrated 1 or 3 hours maintained emergency lighting system available on request.
- Application areas: suitable for the lighting of entrances, walkways, corridors, balconies and for security lighting purposes. The smaller sizes are great for residential interiors, reception areas and small lobbies.



Colour 10 29



## Disco

<b>3421</b>	5x36W 2G11 TC-L		
<b>3422</b>	4x36W 2G11 TC-L		
With integral electronic control gear 220-240V 50/60Hz.			
<b>3480-K30</b>	With 80W LED	3000K 6000lm	
<b>3480-K40</b>	With 80W LED	4000K 6280lm	
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80.			
Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.			



## Mini Disco

<b>3423</b>	1x55W 2GX13 TC-FC		
<b>3424</b>	2x18W 2G11 TC-L		
With integral electronic control gear 220-240V 50/60Hz.			
<b>3482-K30</b>	With 45W LED	3000K 3375lm	
<b>3482-K40</b>	With 45W LED	4000K 3530lm	
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80.			
Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.			



## Micro Disco

<b>3425</b>	1x22W 2GX13 TC-FC		
<b>3426</b>	2x26W G24q-3 TC-DE		
With integral electronic control gear 220-240V 50/60Hz.			
<b>3484-K30</b>	With 30W LED	3000K 2250lm	
<b>3484-K40</b>	With 30W LED	4000K 2350lm	
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80.			
Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.			