

DomoLED



Related products:



DOMOLED Suspension Square P.286-287	DOMOLED Suspension Round P.286-287	DOMOLED Recessed Square P.30-33	DOMOLED Recessed Round P.30-33	DOMOLED Surface Square P.232-233	DOMOLED Surface Round P.232-233	DOMO Square P.100-101	DOMO Round P.100-101
--	---	--	---	---	--	------------------------------------	-----------------------------------

Features

IP20


- Track mounted luminaires.
- Front regressed diffuser Trim made of die cast aluminium.
- Housing made of die formed white coated steel.
- Diffuser made of satin opal acrylic.
- Integrated electronic Driver.
- Mounting installation is easy via Track adaptor which is three circuit universal.
- Dimming versions available upon request.
- Fixture is available in 2 shapes, Round or Square and in 3 sizes.
- Light source is LED.
- Long life LED light source provides IR and UV free emission.
- Designed and manufactured to comply with European standard EN 60598.

Applications

- DomoLED lensed Track mounted down lights provide visually comfortable energy-efficient with general illumination with architecturally sensitive aesthetics. The trim is designed to house a regressed diffuser for optimal performance of wide uniform wash of light and reducing lamp image and eliminate striations in the beam.
- Application areas: offices, entrances, receptions, bathrooms, canopy, corridors, hospitals, retail, residential, hotel, galleries and others.




Colour



DomoLED Track Round

- 6345-K30** With 35W LED 3000K 2100lm
- 6345-K40** With 35W LED 4000K 2275lm


Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80. Leading-Trailing edge dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.



Mini DomoLED Track Round

- 6346-K30** With 25W LED 3000K 1500lm
- 6346-K40** With 25W LED 4000K 1625lm


Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80. Leading-Trailing edge dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.



Micro DomoLED Track Round

- 6347-K30** With 12W LED 3000K 720lm
- 6347-K40** With 12W LED 4000K 780lm


Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80. 1-10V DC dimmable driver option upon request. Other colour temperatures K or CRI are available upon request.



DomoLED Track Square

- 6348-K30** With 35W LED 3000K 2100lm
- 6348-K40** With 35W LED 4000K 2275lm

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80. Leading-Trailing edge dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.



Mini DomoLED Track Square

- 6349-K30** With 25W LED 3000K 1500lm
- 6349-K40** With 25W LED 4000K 1625lm

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80. Leading-Trailing edge dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.



Micro DomoLED Track Square

- 6350-K30** With 12W LED 3000K 720lm
- 6350-K40** With 12W LED 4000K 780lm

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80. 1-10V DC dimmable driver option upon request. Other colour temperatures K or CRI are available upon request.