

DomoLED



Related products:



DOMOLED Track Square P.150-151	DOMOLED Track Round P.150-151	DOMOLED Recessed Square P.30-33	DOMOLED Recessed Round P.30-33	DOMOLED Surface Square P.232-233	DOMOLED Surface Round P.232-233	DOMO Square P.100-101	DOMO Round P.100-101
---	--	--	---	---	--	------------------------------------	-----------------------------------

Features

IP20


- Pendant luminaries
- Front regressed diffuser Trim and Canopy made of die cast aluminium.
- Housing made of die formed white coated steel, Diffuser made of satin opal acrylic.
- Integrated electronic Driver.
- Mounting installation is easy via canopy with inclusive 1 (for micro size) or 3 (for mini or large sizes) suspensions wires with pre-installed 1.5 meter electrical cable.
- Digital dimming and integrated emergency versions available upon request.
- Fixture is available in 2 shapes, Round or Square and in 3 sizes.
- Light source is LED.
- Long life LED light source provides IR and UV free emission.
- Designed and manufactured to comply with European standard EN 60598.

Applications

- DomoLed lensed pendant down lights provide visually comfortable energy-efficient with general illumination and architecturally sensitive aesthetics. The trim is designed to house a regressed diffuser for optimal performance of wide uniform wash of light and reducing lamp image and eliminate striations in the beam.
- Application areas: offices, residential, retail, supermarkets, hospitals, restaurants, hotels entrances, receptions, corridors, task lighting when placed over counter and tables.




Colour



DomoLED Suspension Round

- 7119-K30** With 35W LED 3000K 2100lm
- 7119-K40** With 35W LED 4000K 2275lm


Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80. Leading-Trailing edge dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.



Mini DomoLED Suspension Round

- 7120-K30** With 25W LED 3000K 1500lm
- 7120-K40** With 25W LED 4000K 1625lm



Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80. Leading-Trailing edge dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.



Micro DomoLED Suspension Round

- 7121-K30** With 12W LED 3000K 720lm
- 7121-K40** With 12W LED 4000K 780lm


Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80. 1-10V DC dimmable driver option upon request. Other colour temperatures K or CRI are available upon request.



DomoLED Suspension Square

- 7122-K30** With 35W LED 3000K 2100lm
- 7122-K40** With 35W LED 4000K 2275lm


Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80. Leading-Trailing edge dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.



Mini DomoLED Suspension Square

- 7123-K30** With 25W LED 3000K 1500lm
- 7123-K40** With 25W LED 4000K 1625lm

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80. Leading-Trailing edge dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.



Micro DomoLED Suspension Square

- 7124-K30** With 12W LED 3000K 720lm
- 7124-K40** With 12W LED 4000K 780lm

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80. 1-10V DC dimmable driver option upon request. Other colour temperatures K or CRI are available upon request.