

FioreLED

Designed by **Franco Mirezzi** (Registered)



Features

IP65


- Miniature ground/wall spot light system.
- Base, back plug cover and light head are made of die cast aluminium.
- Includes toughened safety glass, optical lenses, weatherproof durable silicone gasket, stainless steel screws and flexible arm made of brass with external black heat-shrink sheath.
- Superior polyester powder paint resistant to outdoor atmospheric conditions.
- Fixture is available in 2 different bases, Round or Rectangular, with 2 different flexible arms variations.
- Electrical installation includes double cable entry for through wiring.
- Light source is LED.
- Long life LED light source provide IR and UV free emission.
- LED optics use collimating lens made of optical polymer for different beam optics.
- Colour effects can be created by using coloured LEDs by request.
- Designed and manufactured to comply with European standard EN 60598.

Applications

- FioreLED can be mounted on the ground or wall. The Glare shield cap integrated in the design maintains the environment from unpleasant glare light. It has an earth spike (to be ordered separately) for portable or temporary use as well as for additional lighting effect where required due to the arms being fully flexible.
- Application areas: to highlight flowers, trees, plants, woody bushes, illuminate signboards, sculptures, architectural enhancement.



Colour 92




FioreLED Round Base

3437-K30D25	With 5x3W LED 3000K 5x180lm	25°
3437-K40D25	With 5x3W LED 4000K 5x195lm	25°
3437-K30D40	With 5x3W LED 3000K 5x180lm	40°
3437-K40D40	With 5x3W LED 4000K 5x195lm	40°
3437-K30D60	With 5x3W LED 3000K 5x180lm	60°
3437-K40D60	With 5x3W LED 4000K 5x195lm	60°

Passive dissipation, inclusive of integral driver 100-240V 50/60Hz. CRI>80.

Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request. Other colours for base and heads, or colour temperatures K or CRI are available upon request.



FioreLED Rectangular Base

3438-K30D25	With 5x3W LED 3000K 5x180lm	25°
3438-K40D25	With 5x3W LED 4000K 5x195lm	25°
3438-K30D40	With 5x3W LED 3000K 5x180lm	40°
3438-K40D40	With 5x3W LED 4000K 5x195lm	40°
3438-K30D60	With 5x3W LED 3000K 5x180lm	60°
3438-K40D60	With 5x3W LED 4000K 5x195lm	60°

Passive dissipation, inclusive of integral driver 100-240V 50/60Hz. CRI>80.

Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request. Other colours for base and heads, or colour temperatures K or CRI are available upon request.

Accessories



2330 Spike H: 235

For Art. 3437.
In plastic.
The 50mm upper part must stay above ground level according to standards.
Available in colour 10.



2652 Spike H: 220

For Art. 3438.
In plastic.
The 50mm upper part must stay above ground level according to standards.
Available in colour 10.