

Gala



Related products:



DISCO P.382-383 **CIRCO** P.36-39 **QUADRO** P.36-39 **CIRCO Wall** P.334-335 **QUADRO Wall** P.336-337 **ORBIT Round** P.386-387 **ORBIT Square** P.386-387

Features IP66


- Wall/Ceiling luminaries.
- Body and satin opal diffuser are made of injection molded vandal resistance polycarbonate with durable silicon gasket.
- External frame is made in aluminium with countersunk external screws made of stainless steel.
- Superior polyester powder paint is resistant to outdoor atmospheric conditions.
- Available in 3 sizes.
- Simple to install with 2 cable entries to facilitate through wiring.
- Relamping via Allen screws and easy click system removable diffuser.
- Light sources include Fluorescent, Compact and LED.
- Long life LED light source provide IR and UV free emission.
- Dimmable and Emergency versions available upon request.
- Designed and manufactured to comply with European standard EN 60598.

Applications

- Gala include large size up to 685mm x 685mm surface mounted wall or ceiling luminaire to provide large areas of uniform and high quantity of light output. Easy installation and maintenance due to the click system design diffuser made of UV-resistance polycarbonate. Integrated 1 or 3 hours maintained emergency lighting system available on request.
- Application areas: suitable for the lighting of entrances, walkways, corridors, balconies and for security lighting purposes. The smaller sizes are great for residential interiors, reception areas and small lobbies.



Colour 10 29



Gala

3428	3x14/24W G5 T5	
3429	4x14/24W G5 T5	
3430	3x55W 2G11 TC-L	
3431	4x55W 2G11 TC-L	
With integral electronic control gear 220-240V 50/60Hz.		
3481-K30	With 80W LED 3000K 6000lm	
3481-K40	With 80W LED 4000K 6280lm	
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80. Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.		



Mini Gala

3432	1x55W 2GX13 TC-FC	
3433	2x24W 2G11 TC-L	
With integral electronic control gear 220-240V 50/60Hz.		
3483-K30	With 45W LED 3000K 3375lm	
3483-K40	With 45W LED 4000K 3530lm	
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80. Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.		



Micro Gala

3434	1x22W 2GX13 TC-FC	
3435	2x26W G24q-3 TC-DE	
3436	2x18W 2G11 TC-L	
With integral electronic control gear 220-240V 50/60Hz.		
3485-K30	With 30W LED 3000K 2250lm	
3485-K40	With 30W LED 4000K 2350lm	
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80. Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.		