




IKE is a range of moisture and dust proof IP65 fittings suitable for low to medium mounting height installations e.g. industrial buildings, factories and warehouses, dusty and moist environments, or for exterior use in areas not exposed to severe weather conditions, such as under canopy installations, car ports, subways and multi-storey car parks etc..

- Body in polycarbonate light grey colour, auto extinguishing V2 UL94 and 850°C glow wire test resistant, with injected polyurethane double gasket.
- Cover in clear UV stabilized polycarbonate, auto extinguishing V2 UL94 and 850°C glow wire test resistant, internally prismatic with smooth external surface
- AISI 304 stainless steel fast fit brackets for ceiling / suspended installation.
- Internal reflector pre-painted white anti-oxidising steel.
- Standard mains supply wired 230V / 50Hz, other voltages available on request, with capacitor in parallel $\cos\phi \geq 0.9$


Available models for dimmable electronic ballast, fuses, other voltage / frequencies are available on request.


IKE - T8 1x

Lampholder	W	Ilcos	*K	Optic	Colour	Class	Wiring	EEl =	Cosp ≥ 0,9	Code	Notes	☞
G13	1x18W	FD	S	90	I	I	CR	B2	•	05220890	•	
G13	1x36W	FD	S	90	I	I	CR	B2	•	05220990	•	
G13	1x58W	FD	S	90	I	I	CR	B2	•	05221090	•	
G13	1x18W	FD	S	90	I	II	ETRC	A2	•	05221490	•	
G13	1x36W	FD	S	90	I	II	ETRC	A2	•	05221590	•	
G13	1x58W	FD	S	90	I	II	ETRC	A2	•	05221690	•	
G13	1x18W	FD	S	90	II	II	ETRC	A2	•	05227790	•	
G13	1x36W	FD	S	90	II	II	ETRC	A2	•	05227890	•	
G13	1x58W	FD	S	90	II	II	ETRC	A2	•	05227990	•	
G13	1x36W	FD	S	90	I	I	ETRC + EM	A2	•	05222090	•	1
G13	1x58W	FD	S	90	I	I	ETRC + EM	A2	•	05222190	•	1


IKE - T8 2x

Lampholder	W	Ilcos	*K	Optic	Colour	Class	Wiring	EEl =	Cosp ≥ 0,9	Code	Notes	☞
G13	2x18W	FD	S	90	I	I	CR	B2	•	05221190	•	
G13	2x36W	FD	S	90	I	I	CR	B2	•	05221290	•	
G13	2x58W	FD	S	90	I	I	CR	B2	•	05221390	•	
G13	2x18W	FD	S	90	I	II	ETRC	A2	•	05221790	•	
G13	2x36W	FD	S	90	I	II	ETRC	A2	•	05221890	•	
G13	2x58W	FD	S	90	I	II	ETRC	A2	•	05221990	•	
G13	2x18W	FD	S	90	II	II	ETRC	A2	•	05228090	•	
G13	2x36W	FD	S	90	II	II	ETRC	A2	•	05228190	•	
G13	2x58W	FD	S	90	II	II	ETRC	A2	•	05228290	•	
G13	2x36W	FD	S	90	I	I	ETRC + EM	A2	•	05222290	•	1
G13	2x58W	FD	S	90	I	I	ETRC + EM	A2	•	05222390	•	1



☞ Complete with electronic ballast non dimmable 220-240v 50/60hz.

- 1 Single lamp emergency 1hr, maintained, self contained, complete with electronic non dimmable ballast, emergency module and nickel cadmium batteries.



Pair of fast fit strong AISI 304 stainless steel brackets for ceiling mounted or suspended installation.



Technopolymer wide dimension cover clips distribute the loading force for a good seal and ease of operation (6x18W, 10x36W and 12x58W). Clips are lockable using anti-tamper screw accessory (A0412).



Pre-moulded knockout clearance hole in back of body for gland / cable entry.

				IK 09 12J		max 4,6kg			
--	--	--	--	--------------	--	-----------	--	--	--


CLASS I		CLASS II		90	IP 65		FDH 14-35W LUMILUX FH MASTER TLS	FDH 24-80W LUMILUX FQ MASTER TLS	FD 18-58W LUMILUX TL-D
---------	--	----------	--	----	-------	--	---	---	---------------------------------

 I ± 10mm	<table border="1"> <thead> <tr> <th></th> <th>Accm</th> <th>Bmm</th> <th>Imm</th> <th>Lmm</th> </tr> </thead> <tbody> <tr> <td>1/2x18</td> <td>145</td> <td>95</td> <td>330</td> <td>675</td> </tr> <tr> <td>1/2x36</td> <td>145</td> <td>95</td> <td>800</td> <td>1285</td> </tr> <tr> <td>1/2x58</td> <td>145</td> <td>95</td> <td>860</td> <td>1585</td> </tr> <tr> <td>1/2x14</td> <td>145</td> <td>95</td> <td>330</td> <td>675</td> </tr> <tr> <td>1/2x28</td> <td>145</td> <td>95</td> <td>800</td> <td>1285</td> </tr> <tr> <td>1/2x35</td> <td>145</td> <td>95</td> <td>860</td> <td>1585</td> </tr> <tr> <td>1x24</td> <td>145</td> <td>95</td> <td>330</td> <td>675</td> </tr> <tr> <td>1x54</td> <td>145</td> <td>95</td> <td>800</td> <td>1285</td> </tr> <tr> <td>1x49-80</td> <td>145</td> <td>95</td> <td>860</td> <td>1585</td> </tr> </tbody> </table>		Accm	Bmm	Imm	Lmm	1/2x18	145	95	330	675	1/2x36	145	95	800	1285	1/2x58	145	95	860	1585	1/2x14	145	95	330	675	1/2x28	145	95	800	1285	1/2x35	145	95	860	1585	1x24	145	95	330	675	1x54	145	95	800	1285	1x49-80	145	95	860	1585	 I ± 10mm	 PG13.5 Ø6-Ø11 H05RN-F 3Gx1 3x2,5mm²	 OK	 NO NO
	Accm	Bmm	Imm	Lmm																																																			
1/2x18	145	95	330	675																																																			
1/2x36	145	95	800	1285																																																			
1/2x58	145	95	860	1585																																																			
1/2x14	145	95	330	675																																																			
1/2x28	145	95	800	1285																																																			
1/2x35	145	95	860	1585																																																			
1x24	145	95	330	675																																																			
1x54	145	95	800	1285																																																			
1x49-80	145	95	860	1585																																																			




IKE - T5 1x

Lampholder	W	Ilcos	*K	Optic	Colour	Class	Wiring	EEl =	Cosp ≥ 0,9	Code	Notes	
G5	1x14W	FDH	S	90	I	ETRC	A2	•		05223090		•
G5	1x28W	FDH	S	90	I	ETRC	A2	•		05223190		•
G5	1x35W	FDH	S	90	I	ETRC	A2	•		05223290		•
G5	1x24W	FDH	S	90	I	ETRC	A2	•		05223990		•
G5	1x49W	FDH	S	90	I	ETRC	A2	•		05224190		•
G5	1x54W	FDH	S	90	I	ETRC	A2	•		05224090		•
G5	1x80W	FDH	S	90	I	ETRC	A2	•		05224290		•



IKE - T5 2x

Lampholder	W	Ilcos	*K	Optic	Colour	Class	Wiring	EEl =	Cosp ≥ 0,9	Code	Notes	
G5	2x14W	FDH	S	90	I	ETRC	A2	•		05223390		•
G5	2x28W	FDH	S	90	I	ETRC	A2	•		05223490		•
G5	2x35W	FDH	S	90	I	ETRC	A2	•		05223590		•



Complete with electronic ballast non dimmable 220-240v 50/60hz.

THROUGH WIRING

Available upon request complete with two cable glands (5x2.5mm²) subject to minimum order quantities and cost supplement. See diagram below.

W	1x 18	1x 36	1x 58	1x 14	1x 24	1x 28	1x 35	1x 49	1x 54	1x 80	2x 18	2x 36	2x 58	2x 14	2x 28	2x 35
	75	50	32	90	78	55	40	27	33	24	44	25	16	62	32	26
D max (m)	60	70	65	70	60	80	80	55	64	50	50	55	50	55	60	60

ACCESSORIES



Code	Denomination	Description
14430995	A0116 / 36-28-54W	Externert lamellbländskydd Grålackerad aluminium.
14431995	A0116 / 58-35-49-80W	Bländskyddsram Grålackerad aluminium.
14082920	A0412	WIN 02*softglas.