



KHA are high performance IP66 bollards suitable for indoor and outdoor ground installation providing functional and dramatic effect lighting for residential and urban applications, commercial and corporate complexes, parks and gardens. KHA bollards are available in stainless steel or extruded aluminium finished polyester painted matt grey or matt black, supplied in two height options 900mm (KHA 9) or 550mm (KHA 5). KHA bollards are suitable for a variety of light sources and optics providing high performance with zero upward light pollution, combining functional lighting and engineering with contemporary aesthetics making KHA suitable for the most prestigious projects.

- Die cast aluminium ground fixing base.
- Body and top cover available in aluminium or AISI 316 stainless steel for marine applications
- Tecnopolymer wiring connection box, complete with automatic isolating switch, which interrupts supply on opening fitting to provide extra safety.
- High purity aluminium reflector
- Impact resistant UV stabilised clear polycarbonate lamp cover.
- IP68 breather mounted in gear compartment.
- Anti-ageing silicone gaskets.
- Stainless steel external screws.



KHA 5 H 55 cm

Lampholder	W	Ilcos	*K	Optic	Colour	Class	Wiring	EEl =	Cosp ≥ 0,9	Code	Notes
G12	35W	MT	C	81	I			CR	•	05150281	
G12	35W	MT	C	96	I			CR	•	05210896	
G12	70W	MT	C	81	I			CR	•	05150381	
G12	70W	MT	C	96	I			CR	•	05210996	
GX24q-3-4	26÷32W÷42W	FSMH-FSQ	C	81	I	A2	ETRC	•		05150681	EI
GX24q-3-4	26÷32W÷42W	FSMH-FSQ	C	96	I	A2	ETRC	•		05211296	EI
G12	35W	MT	C	04	I			CR	•	05151404	
G12	70W	MT	C	04	I			CR	•	05151504	
GX24q-3-4	26÷32W÷42W	FSMH-FSQ	C	04	I	A2	ETRC	•		05151804	EI

EI Complete with electronic ballast 220-240V 50/60Hz.



KHA 9 H 90 cm

Lampholder	W	Ilcos	*K	Optic	Colour	Class	Wiring	EEl =	Cosp ≥ 0,9	Code	Notes
G12	35W	MT	C	81	I			CR	•	05152081	
G12	35W	MT	C	96	I			CR	•	05211396	
G12	70W	MT	C	81	I			CR	•	05152181	
G12	70W	MT	C	96	I			CR	•	05211496	
GX24q-3-4	26÷32W÷42W	FSMH-FSQ	C	81	I	A2	ETRC	•		05152481	EI
GX24q-3-4	26÷32W÷42W	FSMH-FSQ	C	96	I	A2	ETRC	•		05211796	EI
G12	35W	MT	C	04	I			CR	•	05153204	
G12	70W	MT	C	04	I			CR	•	05153304	
GX24q-3	26÷32W	FSM	C	04	I	A2	ETRC	•		05153604	EI

EI Complete with electronic ballast 220-240V 50/60Hz.

