

# Eye

Colour   
11



## Eye

Rectangular recessed adjustable floodlight for main voltage halogen or metal halide lamps.

### Features

- 0°-60° tilting angle.
- Housing in die cast aluminum.
- Reflector made of super pure aluminum.
- Supplied with safety glass.
- Installation springs suitable for ceiling thickness up to max. 25mm.
- Cable L. 500mm.
- Control gear in pre-wired remote unit has to be ordered separately.
- Designed and manufactured to comply with European standard EN 60598.






### Applications


- Ideal for wall washing and general lighting.
- Application areas: retail, commercial, hospitality, galleries, museum, exhibits, shopping malls.



## Eye

**5056**


70W Rx7s Metal halide   
Control gear not included. To be ordered separately.  
IP40     Safety Glass Included



## Eye

**5057**


150W Rx7s Metal halide   
Control gear not included. To be ordered separately.  
IP40     Safety Glass Included



## Eye

**5058**

Max 200W R7s 117mm Halogen   
IP40     Safety Glass Included



# Micron

Colour   
11



## Micron

Minuscule Recessed Adjustable Downlight

### Features

- 0°-30° vertical tilting adjustability.
- Ceiling Trim body made in die cast aluminum with independent ring made of steel with black powder paint
- Inner black shield to absorb stray light.
- Ceiling springs made of stainless steel suitable for ceiling thickness up to max. 20mm.
- The independent ring allows easy maintenance and lamp replacement.
- SELV (Safety Extra Low Voltage) transformer in pre-wired remote unit has to be ordered separately.
- Designed and manufactured to comply with European standard EN 60598.

### Applications

- Smallest MR16 adjustable downlight with concealed light source for minimal glare.
- Provides one of the smallest available apertures.
- Application areas: retail, window displays, residential, restaurants, hotels, museums, showrooms, exhibits.



The fixing ring can be installed independently, in order to ease installation and maintenance.





0°- 30° vertical tilting adjustability.



## Micron

**5186**

50W 12V GU5.3 MR16   
10W 12V GU5.3 MR16 LED   
Transformer not included. To be ordered separately.  
IP20 