

Mondo



Related products:



MONDO DUE
Track
P.158-161

MONDO DUE
Surface Mounted
P.238-241



Features IP20



- Track mounted spotlight with versatile aiming angle 0°-85° vertical tilting 350° horizontal rotation adjustability.
- Light head and control gear case are made of die cast aluminium.
- Track adaptor - three circuit universal.
- Fixture is available in 2 different sizes.
- Light sources include Low Voltage Halogen, Metal Halide and LED.
- Super pure aluminium reflector with different optic beam.
- Easy relamping via removable front ring by twist-lock action provide user with ultimate flexibility of firm lamp position and acceptance of optical accessories.
- Long life LED light source providing IR and UV free emission.
- For LED versions, other beam optics or colour temperatures K or CRI are available upon request.
- LED optical grade metalized polycarbonate reflector with different beam optics.
- Designed and manufactured to comply with European standard EN 60598.

Applications

- Mondo its simple cylinder design makes it a minimalistic shape with a wide variety of light source options including LEDs and a comprehensive range of optics and accessories to meet most of lighting task requirements.
- Application areas: retail, department stores, museums, galleries, shopping centers, showrooms, residential, restaurants, hotels, exhibitions, window displays.



Colour 10 11 75



Mondo

6245	70W	G12	CDM-T	M.H.		10°
6162	70W	G12	CDM-T	M.H.		40°
6246	100W	G12	CDM-T	M.H.		10°
6193	100W	G12	CDM-T	M.H.		40°

Safety glass included.
With integral electronic control gear 220-240V 50/60Hz.



6163	70W	E27	PAR30	CDM-R	M.H.		15°
6164	70W	GX8.5	CDM-R111	M.H.		15°	

With integral electronic control gear 220-240V 50/60Hz.

6326-K30D15	With 38W	LED	3000K	3000lm		15°	LED
6326-K40D15	With 38W	LED	4000K	3200lm		15°	
6326-K30D24	With 38W	LED	3000K	3000lm		24°	
6326-K40D24	With 38W	LED	4000K	3200lm		24°	
6326-K30D36	With 38W	LED	3000K	3000lm		36°	
6326-K40D36	With 38W	LED	4000K	3200lm		36°	

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz.
CRI>80.

Leading-Trailing edge dimmable driver option upon request.
Other colour temperatures K or CRI are available upon request.




Mondo

6165	12W	E27	PAR30	LED		15°
6166	75W	G53	AR111	Hal.		15°

With integral electronic transformer 220-240/12V 50/60Hz.





Mini Mondo

6243	70W	G8.5	CDM-TC	M.H.		10°
6155	70W	G8.5	CDM-TC	M.H.		40°


Safety glass included.
With integral electronic control gear 220-240V 50/60Hz.

6156	35W	E27	PAR20	CDM-R	M.H.	
6157	35W	GX10	MR16	M.H.		

With integral electronic control gear 220-240V 50/60Hz.

6320-K30D15	With 26W LED	3000K	2000lm		15°	LED
6320-K40D15	With 26W LED	4000K	2200lm		15°	
6320-K30D24	With 26W LED	3000K	2000lm		24°	
6320-K40D24	With 26W LED	4000K	2200lm		24°	
6320-K30D40	With 26W LED	3000K	2000lm		40°	
6320-K40D40	With 26W LED	4000K	2200lm		40°	

Passive dissipation, inclusive of integral LED driver 220-240V 50/60Hz.
CRI>80.
Leading-Trailing edge dimmable driver option upon request.
Other colour temperatures K or CRI are available upon request.



Mini Mondo

6159	35W	GU5.3	MR16	Hal.		
	Max. 15W	GU5.3	MR16	LED		

With integral electronic transformer 220-240/12V 50/60Hz.
Dimmable version is available on request.

6160	7W	E27	PAR20	LED		
-------------	----	-----	-------	-----	--	--

Accessories Table

Coloured Filters	Honeycomb Louvre	Anti-glare Tube	Directional Flaps	Wallwasher Visor
Colours 25, 42, 55, 85	Colour 10	Colours 10, 11, 75	Colour 10	Colour 10

Light Source

Mondo					
G12 CDM-T					
E27 PAR30 CDM-R					
E27 PAR30 LED					
G53 AR111					
G53 AR111 LED					
GX8.5 CDM-R111					
38W LED	2340	2320	2347	2319	2385
Mini Mondo					
26W LED	2695	2693	2694	2692	2386

