





Nippo Round/Square

Directional, adjustable, glare-free.

Features

- → Versatile aiming angle 0°-30° vertical tilting and 350° horizontal rotation adjustability.
- Ceiling trim and lamp holder housing made of die cast aluminium. Designed for optimum heat dissipation.
- → Concealed lamp setting to improve visual comfort and ceiling blending.
- → Reflector made of super pure anodized aluminium.
- → Installation springs suitable for ceiling thickness up to max 25mm.
- → Transformer or control gear (either conventional or electronic) in pre-wired remote unit has to be ordered separately.
- → Designed and manufactured to comply with European standard EN 60598.

Applications

- → A new concept in floodlight designed to be glare-free.
- → Include asymmetrical optics to achieve three dimensional light distribution for wide spread wall washing effect.
- ⇒ Suitable for multiple lamp types, including HID and Halogen.
- → Application areas: retail, commercial, hospitality, galleries, exhibits, residentials.




5665 50W 12V GU5.3 MR16 🗗

10W 12V GU5.3 MR16 LED 4

Transformer not included. To be ordered separately.








Nippo Round

5687 20W GX10 MR16 Metal halide

Electronic control gear not included. To be ordered separately.

IP20 ⊕ 850 🔻 (€





Nippo Square

5731 50W 12V GU5.3 MR16 🖅

10W 12V GU5.3 MR16 LED 🐗

Transformer not included. To be ordered separately.








Nippo Square

5732 20W GX10 MR16 Metal halide

Electronic control gear not included. To be ordered separately.

IP20 ⊕ 850 ▼ (€







hospitality, galleries, exhibits, residenti

formalighting formalighting