



**Optiled**


Wall recessed luminaries

**Features**

- Body is made of thermoplastic.
- Clear tempered glass with special texture for efficient light distribution.
- The die cast aluminum front frame is designed with a slot to enable a wall washer effect.
- Powder coated finish with high corrosion resistance.
- The luminaries are recessed in the body-casing made of thermoplastic. Silicone water tight gasket to achieve IP65.
- Equipped with hard wire cable.
- Installation with counter sink captive screw in stainless steel.
- 230V integral Electronic power supply is included with the Led circuit
- Designed and manufactured to comply with European Standard EN 60598.

**Applications**

- Suitable for outdoor or indoor, are ideal for architectural display, walking signals, as step light or along walls and corridors.





**Optiled - 1**

**3094** 6 White LED 1.2W 220-240V

White LED colour in code 95(cool 6800K), other colours on request.  
Complete with white LED and built-in electronic power supply.  
Supplied hard wired with cable length 300mm.  
Integral LED circuit and Thermoplastic casing for wall recess included.

IP65




**Optiled - 2**

**3095** 6 White LED 1.2W 220-240V

White LED colour in code 95(cool 6800K), other colours on request.  
Complete with white LED and built-in electronic power supply.  
Supplied hard wired with cable length 300mm.  
Integral LED circuit and Thermoplastic casing for wall recess included.

IP65




**Optiled - 3**

**3096** 9 White LED 1.8W 220-240V

White LED colour in code 95(cool 6800K), other colours on request.  
Complete with white LED and built-in electronic power supply.  
Supplied hard wired with cable length 300mm.  
Integral LED circuit and Thermoplastic casing for wall recess included.

IP65



**Accessories**



**IP68 Fast Connector M20**  
( $\varnothing$ 6-12mm)

**2577**

Connection must done inside a recess box.



**IP68 Junction Box**  
( $\varnothing$ 7.5-10.5mm)

**2579**

