

Optiled - Stainless Steel IP65





Optiled - 4

**3097** 24 White LED 4.8W 220-240V

White LED colour in code 95(cool 6800K), other colours on request.  
Complete with white LED and built-in electronic power supply.  
Supplied hard wired with cable length 300mm.  
Integral LED circuit and Thermoplastic casing for wall recess included.

IP65




Optiled - 5

**3098** 24 White LED 4.8W 220-240V

White LED colour in code 95(cool 6800K), other colours on request.  
Complete with white LED and built-in electronic power supply.  
Supplied hard wired with cable length 300mm.  
Integral LED circuit and Thermoplastic casing for wall recess included.

IP65




Optiled - 6

**3099** 24 White LED 4.8W 220-240V

White LED colour in code 95(cool 6800K), other colours on request.  
Complete with white LED and built-in electronic power supply.  
Supplied hard wired with cable length 300mm.  
Integral LED circuit and Thermoplastic casing for wall recess included.

IP65



Optiled - Stainless Steel

Wall recessed luminaires.

Features

- Body is made of galvanized steel.
- Glass toughened frosted/opal painted with silicon water tight gasket.
- The front frame is made of Stainless steel Type AISI 316.
- The luminaires are recessed in a casing made of thermoplastic.
- Silicone water tight gasket to achieve IP65.
- Equipped with hard wire cable.
- Installation with counter sink captive screw in stainless steel.
- 230V integral Electronic power supply is equipped with the Led circuit included.
- Designed and manufactured to comply with European Standard EN 60598.

Applications

- Suitable for outdoor or indoor, are ideal for architectural, display, walking signals, as step light or along walls and corridors.

Accessories



**IP68 Fast Connector M20**  
( $\varnothing$ 6-12mm)  
**2577**

Connection must done inside a recess box.



**IP68 Junction Box**  
( $\varnothing$ 7.5-10.5mm)  
**2579**