


# Optiled Stainless Steel



## Related products:



**OPTILED**  
P.372-373



Thermoplastic Box

## Features IP65

- Wall recessed path light luminaires.
- Front frame made of stainless steel AISI 316 with toughened safety frosted/opal glass and weatherproof durable silicone gasket.
- External counter sink captive screws made of stainless steel.
- Thermoplastic recessed box included.
- Available in 3 versions - round, square and rectangular.
- Easy installations via the included hard wire 600mm long cable type H05-RN-F 3x0,75mm<sup>2</sup>.
- Additional recessed box for pre-installation in concrete during wall construction is optional and available by request.
- Light source is LED.
- Long life LED light source provides IR and UV free emission.
- Designed and manufactured to comply with European standard EN 60598.

## Applications


- The different shapes of these Optiled pathway lights with opal glass give a soft and uniform light distribution. With their minimal size design, they are ideal to fit in any architectural environment and can solve many lighting tasks.
- Application areas: staircases, lighting steps, corridors, walkways and for general guidance in the dark for both indoor and outdoor areas.



Colour 84



120x120



## Optiled 4


**3097-K68** With 2W LED 6800K 100lm

Passive dissipation, inclusive of integral electronic power supply 80-277V 50/60Hz. CRI>80.

Complete with thermoplastic box for wall recess.



93x93



## Optiled 5


**3098-K68** With 2W LED 6800K 100lm

Passive dissipation, inclusive of integral electronic power supply 80-277V 50/60Hz. CRI>80.

Complete with thermoplastic box for wall recess.



143x42



## Optiled 6

**3099-K68** With 2W LED 6800K 100lm

Passive dissipation, inclusive of integral electronic power supply 80-277V 50/60Hz. CRI>80.

Complete with thermoplastic box for wall recess.

## Accessories



**2577 IP68 Fast Connector M20**

( $\varnothing$  6÷12mm)

Connection must be done inside an accessible box.



**2355 IP68 Junction Box**

Junction box up to 3 cables, 3 poles, max. wire section 1.5mm<sup>2</sup>. ( $\varnothing$  6÷10mm)

