

Orbit



Related products:



DISCO
P.382-383

GALA
P.384-385

Features IP65


- Wall/Ceiling luminaires.
- Body is made of die cast aluminium, vandal resistance polycarbonate opal diffusers and weatherproof durable silicone gasket. Countersunk external screws made of stainless steel.
- Superior polyester powder paint is resistant to outdoor atmospheric conditions.
- Available in 2 versions - Round and Square.
- Simple to install with 2 cable entries to facilitate through wiring.
- Light sources include Compact Fluorescent and LED.
- Long life LED light source provide IR and UV free emission.
- Dimmable and Emergency versions available upon request.
- Designed and manufactured to comply with European standard EN 60598.

Applications

- Orbit is an energy saving luminaire. It can be installed by wall or ceiling mounting in all areas both indoor or outdoor. In addition its diffused light emission is designed to also create a halo light effect.
- Application areas: suitable for the lighting of entrances, walkways, corridors, balconies and for security lighting purposes.



Colour



Orbit Round

1098 2x18W G24q-2 TC-DE

1099 2x26W G24q-3 TC-DE

With integral electronic control gear 220-240V 50/60Hz.

1199-K30 With 30W LED 3000K 1800lm LED


1199-K40 With 30W LED 4000K 1950lm

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz.

CRI>80.

Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request.

Other colour temperatures K or CRI are available upon request.



Orbit Square

1100 2x18W G24q-2 TC-DE

1101 2x26W G24q-3 TC-DE

With integral electronic control gear 220-240V 50/60Hz.

1200-K30 With 30W LED 3000K 1800lm LED

1200-K40 With 30W LED 4000K 1950lm

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz.

CRI>80.

Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request.

Other colour temperatures K or CRI are available upon request.