


Palla



Related products:



Palla In-Out Deep P.8-11
Palla Fixed P.12-15
Palla Wallwasher P.16-19
Palla Due P.234-235
Palla Pendant P.284-285



Features

- Track mounted spotlight with versatile aiming angle 0°- 90° vertical tilting of 350° and horizontal rotation adjustability.
- Light head and control gear case are made of die cast aluminium.
- Track adaptor is the three circuit universal type.
- Fixture is available in 3 different sizes.
- The light body is designed for passive cooling.
- Fixture is supplied with pre-installed driver included.
- Dimming drivers available upon request.
- Cover in different finishes is available as an accessory.
- Unalterable light source LED providing excellent fixture to colour consistency within 2-step MacAdam Ellipse tolerance.
- Reflectors field interchangeable in different beam optic are made of either optical grade metalized polycarbonate or of Super pure high quality aluminium.
- Available in Spot, Medium and Flood beam distributions.
- Each optic has been optically engineered to provide a smooth uniform beam, maximizing output and minimizing glare.
- Designed and manufactured to comply with European standard EN 60598 and available to also comply to North American Standard.


Applications

- Palla Track is of a modern design consisting for the purpose to meet the highest requirements of the latest advanced in lighting technology.
- Great for wall washing to illuminate the vertical surface and the upper area of wall.
- Application areas: retail, commercial, galleries, hospitality, exhibits, residential, office lobbies.

IP20




Colour 10 11



Palla Track

6333-K30D16	With 39W LED 3000K 3500lm	■ 16°
6333-K40D16	With 39W LED 4000K 3680lm	■ 16°
6333-K30D26	With 39W LED 3000K 3500lm	■ 26°
6333-K40D26	With 39W LED 4000K 3680lm	■ 26°
6333-K30D36	With 39W LED 3000K 3500lm	■ 36°
6333-K40D36	With 39W LED 4000K 3680lm	■ 36°


Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80.
 Dali/Leading-Trailing edge dimmable drivers options upon request.
 Other colour temperatures K or CRI are available upon request.



Mini Palla Track

6332-K30D16	With 26W LED 3000K 2300lm	■ 16°
6332-K40D16	With 26W LED 4000K 2400lm	■ 16°
6332-K30D26	With 26W LED 3000K 2300lm	■ 26°
6332-K40D26	With 26W LED 4000K 2400lm	■ 26°
6332-K30D36	With 26W LED 3000K 2300lm	■ 36°
6332-K40D36	With 26W LED 4000K 2400lm	■ 36°

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80.
 Dali/Leading-Trailing edge dimmable drivers options upon request.
 Other colour temperatures K or CRI are available upon request.



Micro Palla Track

6331-K30D16	With 16W LED 3000K 1100lm	■ 16°
6331-K40D16	With 16W LED 4000K 1190lm	■ 16°
6331-K30D26	With 16W LED 3000K 1100lm	■ 26°
6331-K40D26	With 16W LED 4000K 1190lm	■ 26°
6331-K30D38	With 16W LED 3000K 1100lm	■ 38°
6331-K40D38	With 16W LED 4000K 1190lm	■ 38°

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80.
 Dali/Leading-Trailing edge dimmable drivers options upon request.
 Other colour temperatures K or CRI are available upon request.