

Palla



Related products:



Palla In-Out Deep P.8-11
Palla Fixed P.12-15
Palla Wallwasher P.16-19
Palla Due P.234-235
Palla Track P.144-145

Features

IP20


- Pendant mounted spotlight luminaire.
- Light head and ceiling canopy are made of die cast aluminium.
- Driver is integral in the ceiling canopy with 3 pole terminal block.
- Top cover options of different coloured finishes.
- Unalterable light source LED providing excellent fixture to colour consistency within 2-step MacAdam Ellipse tolerance.
- Reflectors field interchangeable in different beam optic are made of either optical grade metalized polycarbonate or of Super pure high quality aluminium.
- Available in Spot, Medium and Flood beam distributions.
- Each optic has been optically engineered to provide a smooth uniform beam, maximizing output and minimizing glare.
- Designed and manufactured to comply with European standard EN 60598 and available to also comply to North American Standard.

Applications

- Palla is a Pendant luminaire featuring a clean aesthetic, ideal also for high ceiling spaces and for local 'task' lighting when placed over counters and tables.
- Application areas: retail, departmental stores, galleries, shopping centers, showrooms, residential, restaurants, hotels, exhibitions, window display.




Colour 10 11



Palla Pendant

7127-K30D16	With 39W LED 3000K 3500lm	16°
7127-K40D16	With 39W LED 4000K 3680lm	16°
7127-K30D26	With 39W LED 3000K 3500lm	26°
7127-K40D26	With 39W LED 4000K 3680lm	26°
7127-K30D36	With 39W LED 3000K 3500lm	36°
7127-K40D36	With 39W LED 4000K 3680lm	36°

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80.
 Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.



Mini Palla Pendant

7126-K30D16	With 26W LED 3000K 2300lm	16°
7126-K40D16	With 26W LED 4000K 2400lm	16°
7126-K30D26	With 26W LED 3000K 2300lm	26°
7126-K40D26	With 26W LED 4000K 2400lm	26°
7126-K30D36	With 26W LED 3000K 2300lm	36°
7126-K40D36	With 26W LED 4000K 2400lm	36°

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80.
 Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.



Micro Palla Pendant

7125-K30D16	With 16W LED 3000K 1100lm	16°
7125-K40D16	With 16W LED 4000K 1190lm	16°
7125-K30D26	With 16W LED 3000K 1100lm	26°
7125-K40D26	With 16W LED 4000K 1190lm	26°
7125-K30D38	With 16W LED 3000K 1100lm	38°
7125-K40D38	With 16W LED 4000K 1190lm	38°

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80.
 Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.