

# Circo / Quadro



## Related products:




**DISCO** P.382-383  
**GALA** P.384-385  
**CIRCO Recessed** P.36-39  
**QUADRO Recessed** P.36-39  
**CIRCO Surface** P.334-337  
**QUADRO Surface** P.334-337

## Features IP44

- Pendant luminaires IP44 (dust tight and jetproof).
- Made of injection molded vandal resistance polycarbonate, diffuser finish is in satin opal with high transparency factor with durable silicon gasket.
- The external decorative trim is of coated aluminium.
- Aircraft cable adjustable suspensions with ceiling canopy are included and ready for easy installation - all power supplies are integrally located in the housing.
- Fixture is available in 2 shapes, Round and Square and in 3 sizes.
- No tools required due to the removable diffuser with snap-in catch action fixing.
- Light source include LED.
- Dimmable and emergency versions available upon request.
- Design and manufactured to comply with European standard EN 60598.

## Applications

- Circo & Quadro pendants are architectural decorative luminaires program designed to provide specification-grade quality at prices to fit the budgets for commercial and institutional interiors.
- Application areas: retail, hospitality, offices, schools and community buildings.



## Circo Pendant

**7153-K30** With 80W LED 3000K 6800lm

**7153-K40** With 80W LED 4000K 7100lm


Passive dissipation, inclusive of integral driver 220-240V 50/60Hz.

CRI>80.

Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request.

Other colour temperatures K or CRI are available upon request.

Fluorescent versions available upon request.



## Mini Circo Pendant

**7156-K30** With 45W LED 3000K 3800lm

**7156-K40** With 45W LED 4000K 4000lm


Passive dissipation, inclusive of integral driver 220-240V 50/60Hz.

CRI>80.

Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request.

Other colour temperatures K or CRI are available upon request.

Fluorescent versions available upon request.



## Micro Circo Pendant

**7159-K30** With 30W LED 3000K 2650lm

**7159-K40** With 30W LED 4000K 2850lm


Passive dissipation, inclusive of integral driver 220-240V 50/60Hz.

CRI>80.

Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request.

Other colour temperatures K or CRI are available upon request.

Fluorescent versions available upon request.




#### Quadro Pendant

**7143-K30** With 80W LED 3000K 6800lm

**7143-K40** With 80W LED 4000K 7100lm

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz.  
CRI>80.  
Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request.  
Other colour temperatures K or CRI are available upon request.  
Fluorescent versions available upon request.




#### Mini Quadro Pendant

**7146-K30** With 45W LED 3000K 3800lm

**7146-K40** With 45W LED 4000K 4000lm

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz.  
CRI>80.  
Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request.  
Other colour temperatures K or CRI are available upon request.  
Fluorescent versions available upon request.



#### Micro Quadro Pendant

**7150-K30** With 30W LED 3000K 2650lm

**7150-K40** With 30W LED 4000K 2850lm

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz.  
CRI>80.  
Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request.  
Other colour temperatures K or CRI are available upon request.  
Fluorescent versions available upon request.

