


Ringo




Features

- Track mounted spotlight with versatile aiming angle 0°-90° vertical tilting 350° horizontal rotation adjustability.
- Light head and control gear case are made of die cast aluminium.
- Transformer case is made of heat resistance thermoplastic.
- Stirrup made of die formed galvanized or powder coated steel.
- Track adaptor - three circuit universal.
- Fixture is available in 3 different sizes.
- Light sources include Low Voltage Halogen, Metal Halide and LED.
- Super pure aluminium reflector with different optic beams.
- Easy relamping via removable from back of lamp housing by snap-in catch action and acceptance of optical accessories.
- Long life LED light source providing IR and UV free emission.
- Designed and manufactured to comply with European standard EN 60598.


Applications

- Application areas: retail, department stores, galleries, shopping centers, showrooms, residential, restaurants, hotels, exhibitions, window displays.




Ringo

6144 70W G12 CDM-T M.H. 60°
With integral electronic control gear 220-240V 50/60Hz.




Ringo

6070 70W GX8.5 CDM-R111 M.H.
With integral electronic control gear 220-240V 50/60Hz.




Ringo

6031 75W G53 AR111 Hal.
15W G53 AR111 LED
With integral electronic transformer 220-240V/12V 50/60Hz.




Mini Ringo

6030 70W E27 PAR30 CDM-R M.H.
With integral electronic control gear 220-240V 50/60Hz.



Mini Ringo

6029 12W E27 PAR30 LED



Micro Ringo

6032 35W GU5.3 MR16 Hal.
Max. 15W GU5.3 MR16 LED
With integral electronic transformer 220-240V/12V 50/60Hz.
Dimmable version available upon request.

Accessories Table

	Coloured Filters Colours 25, 42, 55, 85	Reflector Colour 41	UV Filter Colour 41	Honeycomb Louvre Colour 10	Ceiling Base Colour 10
Light Source					
Ringo					
G53 AR111	2175	2178	2181	2184	
Mini Ringo					
E27 PAR30 CDM-R	2174	2177	2180	2183	
E27 PAR30 LED	2174	2177	2180	2183	2049