

Rocket



Related products:



ROCKET
Ceiling
P.388-389



Art. 3087, 3083,
3015, 3014



Art. 3019, 3060,
3065, 3059

Features


IP65

- Wall Surface mounted luminaire.
- Body, frames and rings are made of die cast aluminium.
- Central housing is made of aluminium extrusion with toughened safety glass, weatherproof durable silicone gasket and external screws made of stainless steel.
- Superior polyester powder paint resistant to outdoor atmospheric conditions.
- Front cover is designed to avoid accumulation of dust and water.
- Fixture is available in 3 sizes with the option of 1 or 2 light distributions.
- Electrical installation includes double cable entry.
- Easy relamping via Allen screws.
- Light head on some models are adjustable with a 0° to 25° tilting angle on each vertical side.
- Light sources include Halogen, Compact Flu., Metal Halide and LED.
- Long life LED light source provides IR and UV free emission.
- Superpure aluminium reflector with different beam optics options.
- Colour effects can be created upon request by using colour filters or LEDs.
- Designed and manufactured to comply with European standard EN 60598.

Applications

- Rocket wall mounted luminaire has a simple modernistic appearance making it ideal for today's architectural developments. Provides the option of the Up/Down light version that gives a special narrow beam light effect or a personalized application, or with adjustable light head tilting floodlight providing a high light level of on the illuminated surface.
- Application areas: safety and security task lighting solutions, facades, entrances, walkways, corridors, outdoor or indoor.

Colour | 10 | 29




Mega Rocket Wall Up & Down

3086 2x42W GX24q-4 TC-TE
With integral electronic control gear 220-240V 50/60Hz.

Mega Rocket Wall Up & Down Adjustable

3087 2x70W G12 CDM-T
With integral conventional control gear 230V 50Hz.
Adjustable angle 20°.
150W CDM-T version available upon request.




Mega Rocket Wall Up or Down

3082 1x42W GX24q-4 TC-TE
With integral electronic control gear 220-240V 50/60Hz.

Mega Rocket Wall Up or Down Adjustable

3083 1x70W G12 CDM-T
With integral conventional control gear 230V 50Hz.
Adjustable angle 20°.
150W CDM-T version available upon request.





Rocket Wall Up & Down

3010	2x12W E27 PAR30 LED	H: 315
3012	2x26W GX24q-3 TC-TE	H: 450

With integral electronic control gear 220-240V 50/60Hz.

3503-K30D15	With 2x25W LED 3000K 2x1500lm	H: 450	15°	LED
3503-K40D15	With 2x25W LED 4000K 2x1800lm	H: 450	15°	
3503-K30D30	With 2x25W LED 3000K 2x1500lm	H: 450	30°	
3503-K40D30	With 2x25W LED 4000K 2x1800lm	H: 450	30°	
3503-K30D45	With 2x25W LED 3000K 2x1500lm	H: 450	45°	
3503-K40D45	With 2x25W LED 4000K 2x1800lm	H: 450	45°	

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz.

CRI>80.

Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request.

Other colour temperatures K or CRI are available upon request.




Rocket Wall Up & Down Adjustable

3019	2x35W G8.5 CDM-TC	H: 450	15°
3060	2x35W G8.5 CDM-TC	H: 450	55°

With integral conventional control gear 230V 50Hz.

Adjustable angle 25°.



Rocket Wall Up or Down

3062	1x12W E27 PAR30 LED
3064	1x26W GX24q-3 TC-TE


With integral electronic control gear 220-240V 50/60Hz.

Rocket Wall Up or Down Adjustable

3065	1x35W G8.5 CDM-TC	15°
3059	1x35W G8.5 CDM-TC	55°

With integral conventional control gear 230V 50Hz.

Adjustable angle 25°.



Mini Rocket Wall Up & Down

3017	2x7W E27 PAR20 LED	H: 300
-------------	--------------------	--------

3504-K30D25	With 2x18W LED 3000K 2x1200lm	H: 300	25°	LED
3504-K40D25	With 2x18W LED 4000K 2x1300lm	H: 300	25°	
3504-K30D45	With 2x18W LED 3000K 2x1200lm	H: 300	45°	
3504-K40D45	With 2x18W LED 4000K 2x1300lm	H: 300	45°	
3504-K30D55	With 2x18W LED 3000K 2x1200lm	H: 300	55°	
3504-K40D55	With 2x18W LED 4000K 2x1300lm	H: 300	55°	

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz.

CRI>80.

Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request.

Other colour temperatures K or CRI are available upon request.




Mini Rocket Wall Up & Down Adjustable

3015	2x35W GU5.3 MR16 Hal.	Adjustable angle 20°.
-------------	-----------------------	-----------------------

With integral electronic transformer 220-240/12V 50/60Hz.

Adjustable angle 20°.



Mini Rocket Wall Up or Down

3016	1x7W E27 PAR20 LED
-------------	--------------------

Mini Rocket Wall Up or Down Adjustable

3014	1x35W GU5.3 MR16 Hal.	Adjustable angle 20°.
-------------	-----------------------	-----------------------

With integral electronic transformer 220-240/12V 50/60Hz.

Adjustable angle 20°.

