

Scudo

Designed by **Franco Mirezzi**



Related products:



SCUDO
P.398-401



SCUDO
Ceiling Recessed
P.368-369



SCUDO RAMP
Wall Recessed
P.370-371

Features

IP65/IP66


- Surface mounted luminaire.
- Body is made of die cast aluminium with toughened thermal shock glass diffuser or frosted polycarbonate diffuser. Weatherproof durable silicone gasket with external screws made of stainless steel.
- Grid option is made of die cast aluminium to protect the glass from accidental knocks.
- Front cover is designed to avoid accumulation of dust and water.
- Superior polyester powder paint is resistant to outdoor atmospheric conditions.
- Easy relamping via Allen screws.
- Light sources include Metal Halide, Compact Fluorescent and LED.
- Long life LED light source provide IR and UV free emission.
- Superpure aluminium reflector.
- Designed and manufactured to comply with European standard EN 60598.

Applications

- Scudo wall mounted floodlights have a frosted glass accessory to give a soft and uniform light distribution.
- Application areas: suitable for lighting of sports halls, indoor swimming pools, under canopies, garages and most varied spaces both indoor or outdoor.



Colour | 10 | 29



Scudo Wall

3391 26W G24q-3 TC-DE With frosted polycarbonate diffuser. With integral electronic control gear 220-240V 50/60Hz.

3491-K30 With 30W LED 3000K 1800lm

3491-K40 With 30W LED 4000K 1950lm

With frosted polycarbonate diffuser. Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80. Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.


IP65 IK09



Art.3392, 3235



Art.3492



Scudo Wall Fixed

3392 26W G24q-3 TC-DE

3235 35W G12 CDM-T M.H.

With clear glass. With integral electronic control gear 220-240V 50/60Hz.

IP66 IK07

3492-K30 With 30W LED 3000K 1800lm

3492-K40 With 30W LED 4000K 1950lm

With frosted glass. Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80. Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.


IP66



Art.3393, 3237



Art.3493



Scudo Wall Fixed with Grid

3393 26W G24q-3 TC-DE

3237 35W G12 CDM-T M.H.

With protection grid and clear glass. With integral electronic control gear 220-240V 50/60Hz.

IP66 IK07

3493-K30 With 30W LED 3000K 1800lm

3493-K40 With 30W LED 4000K 1950lm

With protection grid and frosted glass. Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80. Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.

IP66

Accessories



2618 Frosted glass