

Scudo

Designed by **Franco Mirezzi**



Related products:




SCUDO
Wall
P.402-403



SCUDO
Ceiling Recessed
P.368-369



SCUDO RAMP
Wall Recessed
P.370-371




Features IP66



- Wall/Ground or Pole Floodlight.
- Made of die cast aluminium, with toughened safety glass, weatherproof durable silicone gasket and external screws made of stainless steel.
- Superior polyester powder paint is resistant to outdoor atmospheric conditions.
- Front cover is designed to avoid accumulation of dust and water.
- Fixture is available in versions for mounting in ground, wall and pole.
- Electrical installation includes the option for single or double cable entries for through wiring.
- Easy relamping via Allen screws.
- Light sources include Metal Halide, Compact Fluorescent and LED.
- Long life LED light source provide IR and UV free emission.
- Superpure aluminium reflectors with different beam optics.
- Light head includes scaling for vertical and horizontal adjustability and mechanical locking system to ensure aiming stability.
- Designed and manufactured to comply with European standard EN 60598.

Applications

- Scudo floodlights with the range of accessories can be mounted on the ground, wall, wall extension, ceiling, pole top and pole side. The frosted glass accessory gives a soft and uniform light distribution.
- Application areas: to illuminate buildings, landmark facades, large signboards, sculptures, architectural enhancement and most varied spaces both indoor or outdoor.



Colour 10 29




Scudo Wall / Ground

3220 70W RX7s HIT-DE M.H.

3206 150W RX7s HIT-DE M.H.

With clear glass.
With integral electronic control gear 220-240V 50/60Hz.
IK07




Scudo Wall / Ground with Grid

3221 70W RX7s HIT-DE M.H.

3222 150W RX7s HIT-DE M.H.

With protection grid and clear glass.
With integral electronic control gear 220-240V 50/60Hz.
IK07




Scudo Wall

- 3389** 26W G24q-3 TC-DE
- 3223** 35W G12 CDM-T M.H.

With clear glass.
With integral electronic control gear 220-240V 50/60Hz.


IK07



Scudo Wall

- 3489-K30** With 30W LED 3000K 1800lm **LED**
- 3489-K40** With 30W LED 4000K 1950lm

With frosted glass.
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz.
CRI>80.
Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request.
Other colour temperatures K or CRI are available upon request.




Scudo Wall with Grid

- 3390** 26W G24q-3 TC-DE
- 3225** 35W G12 CDM-T M.H.

With protection grid and clear glass.
With integral electronic control gear 220-240V 50/60Hz.

IK07





Scudo Wall with Grid

- 3490-K30** With 30W LED 3000K 1800lm **LED**
- 3490-K40** With 30W LED 4000K 1950lm



With protection grid and frosted glass.
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz.
CRI>80.
Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request.
Other colour temperatures K or CRI are available upon request.

Accessories





- 2508 Pole mounted bracket set**
Ø102mm

- 2507 Pole mounted bracket set**
Ø120mm
For one fixture.
Art. 3206, 3220, 3221, 3222.
Available in colours 10, 29.



- 2563 Pole mounted bracket set**
Ø102mm

- 2564 Pole mounted bracket set**
Ø120mm
For two fixtures.
Art. 3206, 3220, 3221, 3222.
Available in colours 10, 29.



- 2509 Pole mounted bracket set**
Ø102mm

- 2510 Pole mounted bracket set**
Ø120mm
For one or two fixtures.
Art. 3223, 3225, 3389, 3390, 3489, 3490.
Available in colours 10, 29.



- 2618 Frosted glass**



- 2577 IP68 Fast Connector M20**
(Ø 6÷12mm)
For Art. 3223, 3225, 3389, 3390, 3489, 3490.