

Sumo

Designed by **Simon Fisher** (Patented)



Ceiling base for power supply and suspension wire

Features IP20/IP40


- Pendant luminaire series of symmetric or asymmetric light distribution.
- Metal Halide light source versions are with shade and safety glass holder made of die cast aluminium.
- Compact Fluorescent light source version is with shade made of injection molded acrylic with satin finish.
- Control gear housing in thermoplastic material.
- The fixtures are supplied ceiling cup and with pre-installed 1.5 meter electrical cable with 2 x 1.5 meter of pendant steel wires.
- Easy relamping by removing safety glass frame via Allen key.
- Light sources include Metal Halide and Compact Fluorescent.
- Super pure aluminium reflector with different light distribution symmetric and asymmetric.
- Designed and manufactured to comply with European standard EN 60598.

Applications

- Sumo is an innovative concept of Pendant fixture design that allows the functionality of both down lighting and wall washing keeping a uniform appearance, addressing the increasing interest shown by specifiers in lighting that, through its unique design, brings character and individuality to a space. The version with decorative acrylic shade while meets the energy saving choice, guarantees performance, efficiency and comfort in all applications.
- Application areas: retail, department stores, galleries, shopping centers, showrooms, schools, community buildings, supermarkets residential, restaurants, factories.



Colour 17 92




Sumo Asymmetrical Optic

7039 70W RX7s M.H.

7040 150W RX7s M.H.

Asymmetrical reflector in satin superpure anodized aluminium. Safety glass included. With integral electronic control gear 220-240V 50/60Hz.

IP40




Sumo Symmetrical Optic

7043 70W RX7s M.H.

7044 150W RX7s M.H.

Symmetrical reflector in satin superpure anodized aluminium. Safety glass included. With integral electronic control gear 220-240V 50/60Hz.

IP40




Sumo Adjustable Light Beam Angle

7047 70W G12 CDM-T M.H.

7048 150W G12 CDM-T M.H.

Symmetrical reflector in satin superpure anodized aluminium, with adjustable beam. Safety glass included. With integral electronic control gear 220-240V 50/60Hz.

IP40



Sumo PL

7050 42W GX24q-4 TC-TE

Satin finish acrylic diffuser. With integral electronic control gear 220-240V 50/60Hz. Available in colour 17 only.

IP20