

# Trafo

Designed by **Franco Mirezzi**



## Features

IP65


- Wall and pole mounted light system.
- Body visor housing and ribbed LED dissipator are made of die cast aluminium, with weatherproof silicone gasket and concealed stainless steel screws.
- Post is made of extruded aluminium.
- Superior polyester powder paint is resistant to outdoor atmospheric conditions.
- The safety glass is fitted within the luminaire which makes it easy to clean.
- Easy installation via the included hard wire rubber cable and IP67 fast connector.
- Light source is LED.
- Long life LED light source provides IR and UV free emissions.
- Designed and manufactured to comply with European standard EN 60589.

## Applications

- Trafo is an extremely compact designed outdoor luminaire. Its appearance blends into any exterior design to provide lighting designers and architects many application possibilities. It is inclusive of state of the art lighting technology with asymmetrical single or double sided lighting distribution to illuminate downward on the ground. The wall versions could also be light mark facade luminaires with single or double sided light emission.
- Application areas: landscapes, parks, walkways, pathways, walls, entrances, golf courses, gardens and bridges.




Colour | 10 | 29



## Trafo Wall Single Up or Down

- 3451-K30** With 9W LED 3000K 420lm
- 3451-K40** With 9W LED 4000K 450lm


Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80. Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.



## Trafo Wall Double Up & Down

- 3452-K30** With 2x9W LED 3000K 2x420lm
- 3452-K40** With 2x9W LED 4000K 2x450lm


Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80. Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.



## Trafo Bollard Single

- 3453-K30** With 9W LED 3000K 420lm H: 600
- 3453-K40** With 9W LED 4000K 450lm H: 600
- 3454-K30** With 9W LED 3000K 420lm H: 1000
- 3454-K40** With 9W LED 4000K 450lm H: 1000

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80. Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.




## Trafo Bollard Double

- 3455-K30** With 2x9W LED 3000K 2x420lm H: 600
- 3455-K40** With 2x9W LED 4000K 2x450lm H: 600
- 3456-K30** With 2x9W LED 3000K 2x420lm H: 1000
- 3456-K40** With 2x9W LED 4000K 2x450lm H: 1000

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80. Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request. Other colour temperatures K or CRI are available upon request.

## Accessories



### 2231 Anchor Bolt Kit

In steel.  
To ditch in concrete.