

IP 44

class II

IK06 1J xx3



# VARIO

design Roberto Fiorato

Wall, ceiling and post mounted luminaire for 45° directed light, for indoor and outdoor lighting, comprising:

- Body and ring manufactured from technopolymer
- Pressed glass diffuser with internal pattern, internally matt
- Polymer gasket
- Stainless steel locking screws
- Vario C version includes a dawn-dusk switch (activation threshold operates between 10 and 50 lux)
- The magnetic ballasts installed in the fluorescent versions are equipped with thermal cut-off device, according to the EN 60598-1:2004 Standard
- 960°C version produced and distributed on French market

Wand- und Deckenleuchte direkt strahlend unter (45°), für Innen- und Außenbereiche, bestehend aus:

- Gehäuse und Ring aus Technopolymer, Glühdraht 750°C (NF EN 60695-2-11:2001)
- Diffusor aus gepresstem Glas, innen mattiert
- Polymerdichtung
- Äußere Schrauben aus Edelstahl
- Die Ausführung (C) sind mit automatischem Dämmerungsschalter ausgerüstet, Einstellbereich 10-50 Lux
- Die magnetischen Vorschaltgeräte der Leuchtstofflampenausführungen sind mit einem Überlastschutz gemäß EN 60598-1:2004 ausgestattet
- Die 960° Ausführung wird nur für den französischen Markt gefertigt und geliefert.





LAMPHOLDER FASSUNG	W	COLOUR CLASS ILCOS FARBE	KLASSE	COLOUR CLASS KELVIN	COS φ ≥ 0,9	EEI	CODE BESTELLNR.	NOTES BEMERKNG. EURO
-----------------------	---	-----------------------------	--------	------------------------	----------------	-----	--------------------	-------------------------

### VARIO

E27	max 1x100w	IAA	BK1	II			<b>007321</b>	
<b>Fluorescent - magnetic ballast 230V 50Hz/Leuchtstofflampen - VVG 230V 50Hz</b>								
G23	2x9w	FSD	BK1	II		≤B2	<b>007325</b>	
GR8	1x16w	FSS	BK1	II	2700	≤B2	<b>007327</b>	



IK06 1J xx3



### VARIO C

<b>Fluorescent - magnetic ballast 230V 50Hz/Leuchtstofflampen - VVG 230V 50Hz</b>								
G23	2x9w	FSD	BK1	II		≤B2	<b>007331</b>	
GR8	1x16w	FSS	BK1	II	2700	≤B2	<b>007333</b>	


IK06 1J xx3



PACKAGE SIZE / VERPACKUNGSMAß

24,5 x 23 x 27 cm  
(master x 1)

DISTANCE BETWEEN FIXING HOLES / BOHRLOCHABSTAND



If information about Kelvin degrees is provided, this means that the lamp is included.  
Bei Angabe der Grad in Kelvin ist die Lampe eingeschlossen.