



Lampada da incasso in vetro cristallo trasparente o satinato bianco con punta in cristallo trasparente.

Low-voltage semi-recessed fixture available in crystal or in satin whit clear tip.


Einbauleuchte aus transparentem Kristallgals oder weiß-satiniert mit klarer Kristallglasspitze.

Spot encastré en verre cristal transparent ou blanc satiné avec la pointe en cristal transparent.

Empotrable en vidrio transparente o satinado blanco con punta en cristal transparente.

Встроенный светильник из прозрачного или белого сатирированного стекла с вставкой из прозрачного стекла.


DAY



◆ DIC max 1x50W-12V-GU5.3
DIC max 1x50W-250V-GU10



1,6 Kg - 4 lbs
foro 9,5 - Opening 3.3/4"



max 1x7W-LED-230V-GU10
max 1x11W-FLUORESCENT-230V-GU10
1x35W-MR-HQI-Brite Spot 230V-GX10



C: Cristallo
Crystal



B: Bianco satinato
Satin white



DAY



pag. 332 > 333


1,6 Kg - 4 lbs
foro 9,5 - Opening 3.3/4"




DAY - GU 5,3 - 50W 38°

Lux		
h	E max	E med
1.00	2028	1219
2.00	507	305
3.00	225	135
4.00	127	76
5.00	81	49


Gamma Angle



IP20 CE



IP43 CE cULus



max 1x7W-LED-230V-GU10
max 1x11W-FLUORESCENT-230V-GU10
1x35W-MR-HQI-Brite Spot 230V-GX10

DIC max 1x50W-12V-GU5.3
DIC max 1x50W-250V-GU10

DEVON 2



pag. 342 > 343


0,48 Kg - 1 lbs
foro 9,5 - Opening 3.3/4"




DEVON 2 - GU 5,3 - 50W 38°

Lux		
h	E max	E med
1.00	2228	1260
2.00	557	315
3.00	248	140
4.00	139	79
5.00	89	50


Gamma Angle



IP20 CE



IP43 CE cULus



max 1x7W-LED-230V-GU10
max 1x11W-FLUORESCENT-230V-GU10
1x35W-MR-HQI-Brite Spot 230V-GX10

DIC max 1x50W-12V-GU5.3
DIC max 1x50W-250V-GU10

DISK



pag. 326 > 327


1,1 Kg - 3 lbs
foro 9,5 - Opening 3.3/4"




DISK - GU 5,3 - 50W 38°

Lux		
h	E max	E med
1.00	2199	1309
2.00	550	327
3.00	244	145
4.00	137	82
5.00	88	52


Gamma Angle



IP20 CE



IP43 CE cULus



max 1x7W-LED-230V-GU10
max 1x11W-FLUORESCENT-230V-GU10
1x35W-MR-HQI-Brite Spot 230V-GX10

DIC max 1x50W-12V-GU5.3
DIC max 1x50W-250V-GU10

DROP



pag. 330 > 331


0,56 Kg - 1.5 lbs
foro 9,5 - Opening 3.3/4"




DROP - GU 5,3 - 50W 38°

Lux		
h	E max	E med
1.00	603	336
2.00	151	84
3.00	67	37
4.00	38	21
5.00	24	13


Gamma Angle



IP20 CE



IP43 CE cULus



max 1x7W-LED-230V-GU10
max 1x11W-FLUORESCENT-230V-GU10
1x35W-MR-HQI-Brite Spot 230V-GX10

DIC max 1x50W-12V-GU5.3
DIC max 1x50W-250V-GU10