

DROP | Design Toso, Massari & Associates



Lampada da incasso in vetro cristallo trasparente o con interno satinato bianco.

Semi recessed fixture with clear glass trim or satin white inside detail.

Einbauleuchte aus transparentem Kristallglas oder transparentem Kristallglas innen satiniert.

Spot encastré en verre cristal transparent ou à l'intérieur blanc satiné.

Empotrable en vidrio transparente o interior satinado blanco.

Встроенный светильник из прозрачного стекла или изнутри из белого сатинированного.

DROP



DIC max 1x50W-12V-GU5.3
DIC max 1x50W-250V-GU10



1,6 Kg - 4 lbs
foro 9,5 - Opening 3.3/4"



max 1x7W-LED-230V-GU10
max 1x11W-FLUORESCENT-230V-GU10
1x35W-MR-HQI-Brite Spot 230V-GX10



C: Cristallo
Crystal



B: Bianco satinato
Satin white



DAY



pag. 332 > 333


1,6 Kg - 4 lbs
foro 9,5 - Opening 3.3/4"




DAY - GU 5,3 - 50W 38°

Lux		
h	E max	E med
1.00	2028	1219
2.00	507	305
3.00	225	135
4.00	127	76
5.00	81	49

Gamma Angle




IP20 CE



max 1x7W-LED-230V-GU10
max 1x11W-FLUORESCENT-230V-GU10
1x35W-MR-HQI-Brite Spot 230V-GX10

IP43 CE cULus



DIC max 1x50W-12V-GU5.3
DIC max 1x50W-250V-GU10

DEVON 2



pag. 342 > 343


0,48 Kg - 1 lbs
foro 9,5 - Opening 3.3/4"




DEVON 2 - GU 5,3 - 50W 38°

Lux		
h	E max	E med
1.00	2228	1260
2.00	557	315
3.00	248	140
4.00	139	79
5.00	89	50

Gamma Angle




IP20 CE



max 1x7W-LED-230V-GU10
max 1x11W-FLUORESCENT-230V-GU10
1x35W-MR-HQI-Brite Spot 230V-GX10

IP43 CE cULus



DIC max 1x50W-12V-GU5.3
DIC max 1x50W-250V-GU10

DISK



pag. 326 > 327


1,1 Kg - 3 lbs
foro 9,5 - Opening 3.3/4"




DISK - GU 5,3 - 50W 38°

Lux		
h	E max	E med
1.00	2199	1309
2.00	550	327
3.00	244	145
4.00	137	82
5.00	88	52

Gamma Angle




IP20 CE



max 1x7W-LED-230V-GU10
max 1x11W-FLUORESCENT-230V-GU10
1x35W-MR-HQI-Brite Spot 230V-GX10

IP43 CE cULus



DIC max 1x50W-12V-GU5.3
DIC max 1x50W-250V-GU10

DROP



pag. 330 > 331


0,56 Kg - 1.5 lbs
foro 9,5 - Opening 3.3/4"




DROP - GU 5,3 - 50W 38°

Lux		
h	E max	E med
1.00	603	336
2.00	151	84
3.00	67	37
4.00	38	21
5.00	24	13

Gamma Angle




IP20 CE



max 1x7W-LED-230V-GU10
max 1x11W-FLUORESCENT-230V-GU10
1x35W-MR-HQI-Brite Spot 230V-GX10

IP43 CE cULus



DIC max 1x50W-12V-GU5.3
DIC max 1x50W-250V-GU10