



Lampada da incasso in vetro cristallo trasparente con interno satinato bianco o totalmente satinato bianco.

Semi-recessed fixture with clear glass trim and satin inside detail or satin white glass.

Einbauleuchte aus klarem Kristallglas, innen weiß satiniert oder weiß-satiniertem Kristallglas.

Spot encastré en verre cristal transparent et à l'intérieur blanc satiné ou entièrement blanc satiné.

Empotrable en vidrio transparente y interior satinado blanco o totalmente satinado blanco.

Встроенный светильник из прозрачного стекла белого сатинированного хрусталя или прозрачного, сатинированный белый изнутри или полностью сатинированный белый.




C: Cristallo  
Crystal



B: Bianco satinato  
Satin white


ONY



◆ DIC max 1x50W-12V-GU5.3  
DIC max 1x50W-250V-GU10



1,6 Kg - 4 lbs  
for 9,5 - Opening 3.3/4"



max 1x7W-LED-230V-GU10  
max 1x11W-FLUORESCENT-230V-GU10  
1x35W-MR-HQI-Brite Spot 230V-GX10





## MIRA 2



pag.336 > 337


0,38 Kg - 1 lbs  
foro 9,5 - Opening 3.3/4"




MIRA 2 - GU 5,3 - 50W 38°

Lux	E max	E med
h		
1.00	2262	1318
2.00	565	330
3.00	251	146
4.00	141	82
5.00	90	53

Gamma Angle




IP20 CE



max 1x7W-LED-230V-GU10  
max 1x11W-FLUORESCENT-230V-GU10  
1x35W-MR-HQI-Brite Spot 230V-GX10

IP43 CE cULus



DIC max 1x50W-12V-GU5.3  
DIC max 1x50W-250V-GU10

## ONY



pag. 322 > 323


1,6 Kg - 4 lbs  
foro 9,5 - Opening 3.3/4"




ONY - GU 5,3 - 50W 38°

Lux	E max	E med
h		
1.00	2168	1265
2.00	542	316
3.00	241	141
4.00	136	79
5.00	87	51

Gamma Angle




IP20 CE



max 1x7W-LED-230V-GU10  
max 1x11W-FLUORESCENT-230V-GU10  
1x35W-MR-HQI-Brite Spot 230V-GX10

IP43 CE cULus



DIC max 1x50W-12V-GU5.3  
DIC max 1x50W-250V-GU10

## POLAR



pag. 324 > 325


0,7 Kg - 2 lbs  
foro 9,5 - Opening 3.3/4"




POLAR - GU 5,3 - 50W 38°

Lux	E max	E med
h		
1.00	1028	592
2.00	257	148
3.00	114	66
4.00	64	37
5.00	41	24

Gamma Angle




IP20 CE



max 1x7W-LED-230V-GU10  
max 1x11W-FLUORESCENT-230V-GU10  
1x35W-MR-HQI-Brite Spot 230V-GX10

IP43 CE cULus



DIC max 1x50W-12V-GU5.3  
DIC max 1x50W-250V-GU10

## SUN



pag. 328 > 329


0,66 Kg - 1.5 lbs  
foro 9,5 - Opening 3.3/4"




SUN - GU 5,3 - 50W 38°

Lux	E max	E med
h		
1.00	2145	1314
2.00	536	329
3.00	238	146
4.00	134	82
5.00	86	53

Gamma Angle




IP20 CE



max 1x7W-LED-230V-GU10  
max 1x11W-FLUORESCENT-230V-GU10  
1x35W-MR-HQI-Brite Spot 230V-GX10

IP43 CE cULus



DIC max 1x50W-12V-GU5.3  
DIC max 1x50W-250V-GU10