



Lampada da incasso in vetro cristallo trasparente o satinato bianco.

Semi recessed fixture with clear glass trim or satin white.

Einbauleuchte aus transparentem Kristallglas oder weiß-satiniertem Kristallglas.

Spot encastré en verre cristal transparent ou blanc satiné.

Empotrable en vidrio transparente o satinado blanco.

Встроенный светильник из прозрачного или белого сатинированного стекла.


SUN



⚠ DIC max 1x50W-12V-GU5.3
DIC max 1x50W-250V-GU10



1,6 Kg - 4 lbs
foro 9,5 - Opening 3.3/4"



max 1x7W-LED-230V-GU10
max 1x11W-FLUORESCENT-230V-GU10
1x35W-MR-HQI-Brite Spot 230V-GX10



C: Cristallo
Crystal



B: Bianco satinato
Satin white



MIRA 2



pag.336 > 337


0,38 Kg - 1 lbs
foro 9,5 - Opening 3.3/4"




MIRA 2 - GU 5,3 - 50W 38°

Lux		
h	E max	E med
1.00	2262	1318
2.00	565	330
3.00	251	146
4.00	141	82
5.00	90	53


Gamma Angle



IP20 CE



IP43 CE cULus



max 1x7W-LED-230V-GU10
max 1x11W-FLUORESCENT-230V-GU10
1x35W-MR-HQI-Brite Spot 230V-GX10

DIC max 1x50W-12V-GU5.3
DIC max 1x50W-250V-GU10

ONY



pag. 322 > 323


1,6 Kg - 4 lbs
foro 9,5 - Opening 3.3/4"




ONY - GU 5,3 - 50W 38°

Lux		
h	E max	E med
1.00	2168	1265
2.00	542	316
3.00	241	141
4.00	136	79
5.00	87	51


Gamma Angle



IP20 CE



IP43 CE cULus



max 1x7W-LED-230V-GU10
max 1x11W-FLUORESCENT-230V-GU10
1x35W-MR-HQI-Brite Spot 230V-GX10

DIC max 1x50W-12V-GU5.3
DIC max 1x50W-250V-GU10

POLAR



pag. 324 > 325


0,7 Kg - 2 lbs
foro 9,5 - Opening 3.3/4"




POLAR - GU 5,3 - 50W 38°

Lux		
h	E max	E med
1.00	1028	592
2.00	257	148
3.00	114	66
4.00	64	37
5.00	41	24


Gamma Angle



IP20 CE



IP43 CE cULus



max 1x7W-LED-230V-GU10
max 1x11W-FLUORESCENT-230V-GU10
1x35W-MR-HQI-Brite Spot 230V-GX10

DIC max 1x50W-12V-GU5.3
DIC max 1x50W-250V-GU10

SUN



pag. 328 > 329


0,66 Kg - 1.5 lbs
foro 9,5 - Opening 3.3/4"




SUN - GU 5,3 - 50W 38°

Lux		
h	E max	E med
1.00	2145	1314
2.00	536	329
3.00	238	146
4.00	134	82
5.00	86	53


Gamma Angle



IP20 CE



IP43 CE cULus



max 1x7W-LED-230V-GU10
max 1x11W-FLUORESCENT-230V-GU10
1x35W-MR-HQI-Brite Spot 230V-GX10

DIC max 1x50W-12V-GU5.3
DIC max 1x50W-250V-GU10