

T5 Fluorescent System



SlimLamp - T5 / Slick - T5
Surface mounted fluorescent system

- Features**
- Housing made in extruded aluminium.
 - End caps made of heat resistance thermoplastic.
 - Diffuser made in prismatic polycarbonate.
 - Integrated electronic control gear.
 - Designed and manufactured to comply with European standard EN 60598.

- Applications**
- Slick-T5 is of slim smooth elegant profile.
 - Designed to suit the under shelf and cove light applications with the advantages of being available in different lengths.
 - Can be linked together by mean of special connectors.
 - The lamp life is up to 10,000 hours making it energy saving advanced technology luminaire.



HP Slim - T5
Surface mounted fluorescent system

- Features**
- Twice light output than Slimlamp in the same length.
 - End caps made of heat resistance thermoplastic.
 - Diffuser made in prismatic polycarbonate.
 - Integrated electronic control gear.
 - Designed and manufactured to comply with European standard EN 60598.

- Applications**
- Double intensity of light and slenderized structure maximize the effect of indirect lighting in cove, valance, display cases.
 - Can be linked together by mean of special connectors.
 - The lamp life is up to 10,000 hours making it energy saving advanced technology luminaire.

Small Size

SlimLamp - T5



14W
21W
28W
35W

Slick - T5



14W
21W
28W
35W

Twice Output

HP Slim - T5



24W
39W
54W



DimSlim - T5
Surface mounted dimmable fluorescent system

- Features**
- End caps made of heat resistance thermoplastic.
 - Diffuser made in prismatic polycarbonate.
 - Integrated electronic dimmable control gear.
 - Designed and manufactured to comply with European standard EN 60598.

- Applications**
- DimSlim is the most undersized dimmable fluorescent lamp in the world. It now offers designers the option of providing a fully dimmable fluorescent lighting system in the smallest spaces.
 - Controlled by a simple wall mounted controller, 2220 or 2221 (2220 intensity control only/ 2221 intensity and color temp. Control, performing a series of combinations/scenes at your pleasure.



SlimLine - T5 / DimSlimLine -T5
Surface mounted fluorescent system

- Features**
- Exclusively designed lamp in special shape.
 - End caps made of heat resistance thermoplastic.
 - Integrated electronic control gear.
 - Designed and manufactured to comply with European standard EN 60598.

- Applications**
- Dark zone between fixtures is covered by the special shape lamp to enjoy continuous lighting effect with SlimLine.
 - Can be linked together by mean of special connectors.
 - The lamp life is up to 10,000 hours making it energy saving advanced technology luminaire.

Dimmable

DimSlim - T5



14W
21W
28W
35W

Dark Zone Free

SlimLine - T5 / DimSlimLine - T5




14W
21W
28W
24W
39W
54W

DimSlim-T5

ART.	14W T5	21W T5	28W T5	35W T5
4012	600	900	1200	1500

T-5 Lamp and diffuser included
IP20

ART.	L
4012	600
4009	900
4010	1200
4011	1500



SlimLine-T5

ART.	14W T5	21W T5	28W T5
4027	580	880	1180
4028	580	880	1100
4029	580	800	1100

SlimLine-T5 (HP)

ART.	24W T5	39W T5	54W T5
4015	500	800	1100
4016	500	800	1100
4017	500	800	1100


Newly developed lamp, is special shape included.

IP20

Dark Zone Free

ART.	A	B	Max. Linkage per circuit
4027	580	500	42
4028	880	800	28
4029	1180	1100	21

ART.	A	B	Max. Linkage per circuit
4015	580	500	25
4016	880	800	15
4017	1180	1100	11



Accessories

Dimming Controller (Brightness & Mood)

- 2 Channels
- Max. Connection: 10 pcs of DimSlim per channel, up to 350W regardless of channel
- Control range: 4 scenes memorized.
- Input power: AC90~240V
- Frequency: 50/60Hz
- Output protocol: PWM 400Hz
- Dimension: (W122 x H122 x D45)mm

Dimming Controller (Brightness)

- 1 Channel
- Max. Connection: 10 pcs of DimSlim per channel
- Control range: 1~14 level of intensity
- Input power: AC90~240V
- Frequency: 50/60Hz
- Output protocol: PWM 400Hz
- Dimension: (W70 x H120 x D38)mm

Direct Connector

2228



Booster

2307



2220 & 2221 is able to connect maximum 10 pcs of DimSlim per channel. But Booster remarkably extends connecting capability. Link Booster at the 10th DimSlim from 2220 or 2221 and then 20pcs more fixtures can be connected.

Power Cord

2222 Length: 1800



DALI/DSI/DMX to DimSlim PWM Translator

2306




Interface DimSlim PWM with any other DALI/DSI/DMX manufactured control proprietary system. - A single translator can handle a total of 3,500 lamp watts - 4 independent PWM output signals for DimSlim - Maximum connecting load for individual output is 10 amps/1750 lamp watts per circuit, or 50 fixtures per channel.

Flexible Connector

2223 Length: 150
2224 Length: 300
2225 Length: 600
2226 Length: 1200
2227 Length: 1800



Availability:
- Translates standard DALI 4 device protocol with DALI
- Translates standard DMX 512 protocol
- Translates DSI protocol
- Volt: AC196~264V
- Frequency: 50/60Hz
- Current: 20 amp - 4mm² terminals
- Mechanical fixing: DIN rail clip lock
- Dimension: (H86 x W209 x D66)mm



Accessories

Direct Connector

2296



Vertical Power Cord Without plug
2586 Length: 1800

Flexible Connector

2585 Length: 150
2358 Length: 300
2501 Length: 600
2502 Length: 1200
2503 Length: 1800



Horizontal Power Cord Without plug
2587 Length: 1800

Power Cord

Without plug
2556 Length: 1800



Protecting Cap
2297

