

Galileo

Designed by **Franco Mirezzi**



Related products:



GALILEO
Pendant/Wires
P.376-379

GALILEO
Pendant/Rods
P.376-379

GALILEO DUE
P.380-381

Features

IP66


- Multi system Floodlight projectors.
- Made of die cast aluminium, with toughened safety glass, weatherproof durable silicone gasket and external screws made of stainless steel.
- Superior polyester powder paint resistant to outdoor atmospheric conditions.
- Front cover is designed to avoid accumulation of dust and water.
- Fixture is available in 2 different sizes with a many version options for ground, wall, ceiling, pendant and others mounting methods.
- Electrical installation option for single or double cable entries.
- Easy relamping via Allen screws.
- Light sources include Metal Halide and LED.
- Long life LED light source provide IR and UV free emission.
- Super pure aluminium reflector with different beam optics.
- Light head includes scaling for vertical and horizontal adjust ability and mechanical locking system to ensure aiming stability.
- Designed and manufactured to comply with European standard EN 60598.

Applications

- Galileo include large scale high power floodlights for H.I.D. lamps with wide or narrow beam light distribution which make it suitable for all architectural applications. The range of accessories available for mounting on the ground, wall, wall extension, ceiling, pole top and pole side. The internal anti-glare shield for glare suppression and visor glare shield cap helps to protect the environment from unpleasant bright light.
- Application areas: to illuminate buildings, landmarks, facades, big signboards, sculptures and architectural element enhancement.



Colour 10 29



Mega Galileo

3264	1x150W G12 CDM-T M.H.		10°
3267	1x150W G12 CDM-T M.H.		40°
3265	1x250W G12 CDM-T M.H.		10°
3268	1x250W G12 CDM-T M.H.		40°
3266	1x250W E40 HQI-T M.H.		10°
3271	1x250W E40 HQI-T M.H.		40°

With integral conventional control gear 230V 50Hz.

3269-K30D45	With 42x1W LED 3000K 3600lm		45°
3269-K40D45	With 42x1W LED 4000K 4400lm		45°

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80.

Other beam optics or colour temperatures K or CRI are available upon request.

Mega Galileo Ceiling


3275	1x150W G12 CDM-T M.H.		10°
3352	1x150W G12 CDM-T M.H.		40°


With integral conventional control gear 230V 50Hz.

3276-K30D45	With 42x1W LED 3000K 3600lm		45°
3276-K40D45	With 42x1W LED 4000K 4400lm		45°

Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80.


Other beam optics or colour temperatures K or CRI are available upon request.






Mega Galileo Wall Single Up or Down

3322	1x150W G12 CDM-T M.H.	10°
3358	1x150W G12 CDM-T M.H.	40°
3323	1x250W G12 CDM-T M.H.	10°
3359	1x250W G12 CDM-T M.H.	40°
3324	1x250W E40 HQI-T M.H.	10°
3360	1x250W E40 HQI-T M.H.	40°
With integral conventional control gear 230V 50Hz.		
3325-K30D45	With 42x1W LED 3000K 3600lm	45° LED
3325-K40D45	With 42x1W LED 4000K 4400lm	45°
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80.		
Other beam optics or colour temperatures K or CRI are available upon request.		



Mega Galileo Wall Double Up & Down

3270	2x150W G12 CDM-T M.H.	10°
3363	2x150W G12 CDM-T M.H.	40°
With integral conventional control gear 230V 50Hz.		
3331-K30D45	With 2x42x1W LED 3000K 2x3600lm	45° LED
3331-K40D45	With 2x42x1W LED 4000K 2x4400lm	45°
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80.		
Other beam optics or colour temperatures K or CRI are available upon request.		




Mini Galileo

3286	1x35W G12 CDM-T M.H.	10°
3288	1x35W G12 CDM-T M.H.	40°
3287	1x70W G12 CDM-T M.H.	10°
3279	1x70W G12 CDM-T M.H.	40°
With integral conventional control gear 230V 50Hz.		
3277-K30D45	With 21x1W LED 3000K 1800lm	45° LED
3277-K40D45	With 21x1W LED 4000K 2200lm	45°
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80.		
Other beam optics or colour temperatures K or CRI are available upon request.		




Mini Galileo Ceiling

3290	1x35W G12 CDM-T M.H.	10°
3353	1x35W G12 CDM-T M.H.	40°
With integral conventional control gear 230V 50Hz.		
3292-K30D45	With 21x1W LED 3000K 1800lm	45° LED
3292-K40D45	With 21x1W LED 4000K 2200lm	45°
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80.		
Other beam optics or colour temperatures K or CRI are available upon request.		



Mini Galileo Wall Single Up or Down

3326	1x35W G12 CDM-T M.H.	10°
3361	1x35W G12 CDM-T M.H.	40°
3327	1x70W G12 CDM-T M.H.	10°
3362	1x70W G12 CDM-T M.H.	40°
With integral conventional control gear 230V 50Hz.		
3328-K30D45	With 21x1W LED 3000K 1800lm	45° LED
3328-K40D45	With 21x1W LED 4000K 2200lm	45°
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80.		
Other beam optics or colour temperatures K or CRI are available upon request.		




Mini Galileo Wall Double Up & Down

3278	2x35W G12 CDM-T M.H.	10°
3366	2x35W G12 CDM-T M.H.	40°
With integral conventional control gear 230V 50Hz.		
3333-K30D45	With 2x21x1W LED 3000K 2x1800lm	45° LED
3333-K40D45	With 2x21x1W LED 4000K 2x2200lm	45°
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz. CRI>80.		
Other beam optics or colour temperatures K or CRI are available upon request.		



Accessories



2509 Pole mounted bracket set
Ø102mm



2510 Pole mounted bracket set
Ø120mm
For one or two fixtures.
For Art. 3264, 3265, 3266, 3267, 3269, 3271 and 3277, 3279, 3286, 3287, 3288.
Available in colours 10, 29.



2592 Visor for Mega Galileo




2593 Visor for Mini Galileo
Available in colours 10, 29



2594 Anti-glare shield for Mega Galileo



2595 Anti-glare shield for Mini Galileo
Available in colour 10



2577 IP68 Fast Connector M20
(Ø 6÷12mm)