

T5 Fluorescent System



SlimLamp - T5 / Slick - T5

Surface mounted fluorescent system

Features

- Housing made in extruded aluminium.
- End caps made of heat resistance thermoplastic.
- Diffuser made in prismatic polycarbonate.
- Integrated electronic control gear.
- Designed and manufactured to comply with European standard EN 60598.

Applications

- Slick-T5 is of slim smooth elegant profile.
- Designed to suit the under shelf and cove light applications with the advantages of being available in different lengths.
- Can be linked together by mean of special connectors.
- The lamp life is up to 10,000 hours making it energy saving advanced technology luminaire.



HP Slim - T5

Surface mounted fluorescent system

Features

- Twice light output than Slimlamp in the same length.
- End caps made of heat resistance thermoplastic.
- Diffuser made in prismatic polycarbonate.
- Integrated electronic control gear.
- Designed and manufactured to comply with European standard EN 60598.

Applications

- Double intensity of light and slendertized structure maximize the effect of indirect lighting in cove, valance, display cases.
- Can be linked together by mean of special connectors.
- The lamp life is up to 10,000 hours making it energy saving advanced technology luminaire.

Small Size

SlimLamp - T5

- 14W
- 21W
- 28W
- 35W



Slick - T5

- 14W
- 21W
- 28W
- 35W



Twice Output

HP Slim - T5

- 24W
- 39W
- 54W



DimSlim - T5

Surface mounted dimmable fluorescent system

Features

- End caps made of heat resistance thermoplastic.
- Diffuser made in prismatic polycarbonate.
- Integrated electronic dimmable control gear.
- Designed and manufactured to comply with European standard EN 60598.

Applications

- DimSlim is the most undersized dimmable fluorescent lamp in the world. It now offers designers the option of providing a fully dimmable fluorescent lighting system in the smallest spaces.
- Controlled by a simple wall mounted controller, 2220 or 2221 (2220 intensity control only/ 2221 intensity and color temp. Control, performing a series of combinations/scenes at your pleasure.



SlimLine - T5 / DimSlimLine -T5

Surface mounted fluorescent system

Features

- Exclusively designed lamp in special shape.
- End caps made of heat resistance thermoplastic.
- Integrated electronic control gear.
- Designed and manufactured to comply with European standard EN 60598.

Applications

- Dark zone between fixtures is covered by the special shape lamp to enjoy continuous lighting effect with SlimLine.
- Can be linked together by mean of special connectors.
- The lamp life is up to 10,000 hours making it energy saving advanced technology luminaire.

Dimmable

DimSlim - T5

- 14W
- 21W
- 28W
- 35W



Dark Zone Free

SlimLine - T5 / DimSlimLine - T5

- 14W
- 21W
- 28W
- 24W
- 39W
- 54W



Slimlamp-T5 & Slick-T5



Slimlamp-T5	
4005	14W T5
4006	21W T5
4007	28W T5
4008	35W T5

T-5 Lamp and diffuser included
IP20

Small Size

ART.	L	Max. Linkage in one line
4005	600	25
4006	900	16
4007	1200	12
4008	1500	10

Maximum wattage in a single line is 350W.




Slick-T5

4001	14W T5
4002	21W T5
4003	28W T5
4004	35W T5

T-5 Lamp and diffuser included
IP20

ART.	L	Max. Linkage in one line
4001	600	25
4002	900	16
4003	1200	12
4004	1500	10

Maximum wattage in a single line is 350W.



No.: Maximum quantity of linkage in one line.

HP Slim-T5




HP Slim-T5	
4018	24W T5
4019	39W T5
4020	54W T5

T-5 Lamp and diffuser included

IP20

ART.	L	Max. Linkage in one line
4018	600	15
4019	900	9
4020	1200	7

Maximum wattage in a single line is 350W.



Accessories



Direct Connector
2059



Flexible Connector

2061	Length: 150
2185	Length: 300
2186	Length: 600
2187	Length: 1200
2188	Length: 1800




Power Cord With Plug

2060
Length: 1800



Hardwire Box
2062



ON/OFF Switch
2246



Accessories



Direct Connector
2059



Flexible Connector

2061	Length: 150
2185	Length: 300
2186	Length: 600
2187	Length: 1200
2188	Length: 1800



Power Cord With Plug

2060
Length: 1800

