

Scudo

Designed by **Franco Mirezzi**




Related products:



SCUDO
P.398-401

SCUDO
Wall
P.402-403

SCUDO RAMP
Wall Recessed
P.370-371



Thermoplastic Box

Features IP66

- Recessed ceiling or wall luminaire.
- Made of die cast aluminium, with toughened thermal-shock glass diffuser, weatherproof durable silicone gasket and external screws made of stainless steel. Thermoplastic recessed box included.
- Superior polyester powder paint is resistant to outdoor atmospheric conditions.
- Shallow installation depth and easy mounting system.
- Easy relamping via Allen screws.
- Ceiling installation via clamping wings for ceiling thickness 10mm to max.40mm.
- Fixtures are available in 2 light distributions: symmetric or asymmetric.
- Light sources include Metal Halide, Compact Fluorescent and LED.
- Long life LED light source provide IR and UV free emission.
- Superpure aluminium reflector.
- Designed and manufactured to comply with European standard EN 60598.

Applications


- Scudo recessed ceiling or wall mounted floodlight providing a high level of illuminance on the illuminated surface.
- Application areas: for many outdoor ceiling functional lighting solutions, canopies, hotel entrances, gymnasiums, indoor swimming pools, garages.



Colour



294x294




Scudo Ceiling Recessed Symmetric

3395	26W	G24q-3	TC-DE	
3228	32W	GX24q-3	TC-TE	
3229	70W	RX7s	HIT-DE	M.H.
3230	150W	RX7s	HIT-DE	M.H.

With clear glass.
Complete with thermoplastic box for ceiling recess.
Control gear not included. To be ordered separately.
IK07



294x294




Scudo Ceiling Recessed Asymmetric

3396	26W	G24q-3	TC-DE	
3231	32W	GX24q-3	TC-TE	
3232	70W	RX7s	HIT-DE	M.H.
3233	150W	RX7s	HIT-DE	M.H.

With clear glass.
Complete with thermoplastic box for ceiling recess.
Control gear not included. To be ordered separately.
IK07



294x294



Scudo Ceiling Recessed Asymmetric

3495-K30	With 30W LED	3000K	1800lm	
3495-K40	With 30W LED	4000K	1950lm	

With frosted glass.
Passive dissipation, inclusive of integral driver 220-240V 50/60Hz.
CRI>80.
Complete with thermoplastic box for ceiling recess.
Dali/Leading-Trailing edge/1-10V DC/PWM dimmable drivers options upon request.
Other colour temperatures K or CRI are available upon request.

Accessories



2605	Waterproof box	IP66	26W	(EL)	TC
2606	Waterproof box	IP66	32W	(EL)	TC
2603	Waterproof box	IP66	70W	(EL)	HIT
2604	Waterproof box	IP66	150W	(EL)	HIT

With electronic control gear 220-240V 50/60Hz.
For details, please see p.426.